

RECEIVED

NOV 14 '90

O. C. D.
ARTESIA, OFFICE

KERR MCGEE CORPORATION
ANGEL RANCH (MORROW ATOKA)
UNIT LETTER K
1980' FSL & 1980' FWL
SEC. 25, 19S, R27E
EDDY COUNTY, NEW MEXICO

10/19/90 MIRU POOL WELL SERVICE. NU BOP. PU ON TBG.
HAD 19 PTS WEIGHT ON INDICATOR. TOH W/ 2424' OF 2 3/8" TBG.
HAVE 2 3/8" COLLAR LOOKING UP. TIH W/ 3.875" OD OVERSHOT TO 160'.
TIGHT. POOH. SDFN.

10/20/90 TIH W/ 3 3/4" OD OVERSHOT. TIH AND CAUGHT FISH.
RELEASED PACKER. TOH W/ TBG. AND PACKER. RU WIRELINE. SET CIBP
@ 10,100'. RD WIRELINE. TIH W/ 2 3/8" TBG. SD FOR WEEKEND.

10/21/90 S.I. FOR WEEKEND

10/22/90 S.I. FOR WEEKEND

10/23/90 WITH TBG @ 10,100' LOADED CSG W/ MUD LADEN FLUID.
SPOTTED 10 SX CLASS "H" @ 10,200'. POH W/ 39 JTS. SPOTTED 10 SX CL
H AT 8995'. LD 14 JTS. REVERSE CIRC. CLEAN. TOH.
JOHNNY ROBINSON W/NMOCD WAS ADVISED OF THE PLUGS.

10/24/90 WELDED ON PULL NIPPLE. PU ON CSG. FOUND IT PARTED
WEIGHT - 43,000#. INDICATED CASING PARTED AT 4200'. POH 30 + OR -.
TIH AND RESET CASING IN WELLHEAD. TIH W/ 2 3/8" TBG. FELT A JERK
@ 4240'. TIH TO 8550'. SPOTTED 35 SX CLASS C AS PER INSTRUCTIONSS
FROM GARY WILLIAMS W/ NMOCD. MAC WILLIAMS WITH NMOCD ADVISED THAT
THE PLUG @ 5950' SHOULD BE HANDLED AS FOLLOWS: WITH TBG. @ 5850' + OR
- PERF 6 HOLES @ 5900' USING A THRU TBG. GUN, SPOT 75 SX @ 5950'.

10/25/90 WITH TBG @ 5850' RU POOL WIRELINE. PERFORATE 6
HOLES @ 5900'. RD WIRELINE. TIH TO 5950''. SPOTTED 75 SX CLASS H
@ 5450'. TOH W/ TBG. TOOH W/ 100 JTS OF 4 1/2" CASING. (4054.29')
(39 JTS OF 13.5#/FT. & 61 JTS OF 11.6#/FT.) BOTTOM CSG. COLLAR
WAS SPLIT AND NEXT 2 COLLARS WERE BADLY CORRODED. TIH W/ TBG. SPOTTED
45 SX CLASS H CMT PLUG @ 4100'. TOOH W/ 12 STANDS TBG. SDON.

10/26/90 TIH W/ TBG. TAG PLUG @ 4050' (TOP OF 4 1/2")
PUMP 45 SX CLASS "H" CMT. PLUG. WAIT 4 HOURS. TAGGED @ 3939'
SPOTTED 45 SX CLASS "H" @ 3270'. SPOTTED 50 SX CLASS "H" @ 3050'.

10/27/90 TAG CMT PLUG @ 2883'. TOOH TO 2440'. PUMPED
40 SX. PLUG. TOP @ 2320'. TOOH TO 1525' PUMPED 40 SX PLUG. TOP @
1425'. TOOH TO 475' PUMPED 40 SX PLUG. TOP @ 375'. TOOH TO 30'
PUMPED 10 SX SURFACE PLUG. CUT OFF WELLHEAD. WELDED ON LOCATION
MARKER. FILL IN CELLAR.