

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-73

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	/
LAND OFFICES	
OPERATOR	/

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.
L-4222

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>		RECEIVED	7. Unit Agreement Name
2. Name of Operator Gulf Oil Corporation /		OCT 22 1981	8. Farm or Lease Name Eddy "GZ" State Com
3. Address of Operator P. O. Box 670, Hobbs, NM 88240		O. C. D.	9. Well No. 1
4. Location of Well UNIT LETTER <u>I</u> 1980 FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>12</u> TOWNSHIP <u>19S</u> RANGE <u>27E</u> NMPM.		ARTESIA, OFFICE	10. Field and Pool, or WHdcat Morrow
15. Elevation (Show whether DF, RT, GR, etc.) 3521' GL		12. County Eddy	

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <u>Abandon Morrow sands, recomplete Upper Morrow</u> <input checked="" type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

POH with packer and tubing. Set CIBP at 10,525'. Perf 10,322-25' with (2) 1/2" JHPF and 10,346-54', 10,382-98', 10,458-64' with (1) 1/2" JHPF (40 holes). Spot 15% double inhibited Morrow acid 10,465'-10,300'. Swab and test.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED R.D. Pitre TITLE Area Engineer DATE 10-21-81

APPROVED BY Mrs. Wilbur TITLE OIL AND GAS INSPECTOR DATE OCT 26 1981

CONDITIONS OF APPROVAL, IF ANY: