

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

AUG - 7 1978

O. C. C.
ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State ☒	Fed ☐
5. State Oil & Gas Lease No.	
L - 3647	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☐ GAS WELL ☒ OTHER-	7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation ✓	8. Farm or Lease Name Siegest JS St. Com
3. Address of Operator 207 South 4th Street - Artesia, NM 88210	9. Well No. 1 1
4. Location of Well UNIT LETTER C 660 FEET FROM THE North LINE AND 1980 FEET FROM THE West LINE, SECTION 30 TOWNSHIP 19S RANGE 24E NMPM.	10. Field and Pool, or Wildcat Wildcat Morrow
15. Elevation (Show whether DF, RT, GR, etc.) 3813' GR	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	OTHER Run 5½" csq & Perf ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 8643' - Ran 5½" casing as follows: 43 joints 17# K-55 (1750'), 162 jts 15.5# K-55 (6702') and 6 jts of 17# K-55 (250') (Total 8602') set at 8602'. 1-Guide shoe at 8602', Diff-Fill Float Collar at 8560' and 8 centralizers. Cemented as follows: 250 gallons mud flush, 450 sacks of Howco Lite, 5/10% Halad 22, 3/10% CFR-2, 5#/sack KCL tailed in w/100 sacks of Class H 5/10% Halad 22, 3/10% CFR-2, 5#/sack KCL displaced w/40 bbls 2% KCL water. PD 11:20 AM 7-23-78. WOC. Ran Temperature Survey and found top of cement at 6000'. WLPBTD 8549'. WOC and tested to 1500#. OK.
TD 8643'; WLPBTD 8549'. WIH w/Tubing Conveyed Gun, Baker Lok-Set packer on 2-3/8" tubing at 8412', set packer at 8418'. Perforated 8435-8462' w/88 .50" holes 4 spf as follows: 8435-8453 (72 holes), 8458-8462' (16 holes (Total 88 holes. GTS in 2 minutes. Well cleaned up and flowed 440# on 1/2" choke = 2.7 MMCPPD.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christie Tomlinson TITLE Geol. Secty DATE 8-3-78

APPROVED BY W.A. Gresset TITLE SUPERVISOR, DISTRICT II DATE AUG - 8 1978
CONDITIONS OF APPROVAL, IF ANY: