Form 9-331 (May 1963)	N. M. DONC. C.	SUBMIT IN TE ICATE	Form a	24 75 SF proved. Bureau No. 42-R1424.	
DEPARTMENT OF THE INTERIOR (Other Instruction of the Geological Survey			N.M. 77		
(Do not use this form for Use "AP	IOTICES AND REPORTS proposals to drill or to deepen or plu PLICATION FOR PERMIT—" for suc	Back to a different reservoir.	G. IF INDIAN, ALL	LOTTEE OR TRIBE NAME	
1. OIL GAS WELL GAS WELL OTHER 2. NAME OF OPERATOR		SEP 1 2 1978	7. UNIT AGREEMENT NAME Gerdner Draw Unit 8. FARM OR LEASE NAME		
Phoenix Resources Con 3. ADDRESS OF OPERATOR	spany V	O. C. C.	9. WELL NO.		
One Marienfeld Place	, Suite 290, Midland, tion clearly and in accordance with s	Texas 79701 Iny State requirements.*	10. FIELD AND PO	OL, OR WILDCAT	
At surface Unit Letter "J", 1980' FEL, 1700' FSL, Section 20, T-19-S, R-21-E				Nildert 11. sec., t., b., M., or blk. and survey or abba	
14. PERMIT NO.	15. BLEVATIONS (Show whether	DF. RT. GR. etc.)	•	T-19-S, R-21-E	
	4380' GR		Eddy	New Mexico	
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data					
NOTICE OF INTENTION TO:			JENT REPORT OF:		
TEST WATER SHUT-OFF	PULL OB ALTER CASING MULTIPLE COMPLETE ABANDON® CHANGE PLANS	(Nore: Report results	ALTER ABAND Test § Carl	etion on Well	
17. DESCRIBE PROPOSED OR COMPLETI	D OPERATIONS (Clearly state all perti- irectionally drilled, give subsurface 1	Completion or Recompl nent details, and give pertinent dates, ocations and measured and true vertice	including estimate	d date of starting any	
nent to this work.) *		8# Casing. Cemented w			
w/3% CaCl ₂ a	nd 100 sks RSC-12-3.	Ran temp. survey - Top	of cement (9 150'. Ran	
8 yds pea gr 1500# - held		ent per yard. WOC 18 1	hrs. Pressi	ire test to	
7-12-78 Ran 44 jts.	8 5/8", 24 # , K-55 casi	ng. Set @ 1794'. Pum			
Kolite, 1/4#	cello flake, 4 1/2% g	RFC, 1140 sks 50/50 po el, 2% CaCl ₂ . Ran tem	D. SUTVey -	Top of	
coment 0 113	0'. STAGE 2: Cemente	d w/50 sks Člass "C" w	/4% CaCl.	WOC. Tagged	
top of cemen	t 8 1129'. STAGE 4:	d w/50 sks Class "C" w Cemented with 50 sks C	/4% CaCl2. lass "C" w//	WOC. Tagged 4% CaCl	
7-13-78 One inching	with 50 sks Class "C"	w/4% CaCl ₂ . Tagged to	p of cement	€ 1090 [€] .	
STAGE 5: Com RFC - tagged	ented w/50 sks Class " cement # 960'. STAGE	C" w/4% CaCl ₂ . STAGE	5: Cemented s RFC - tag	w/100 sks wed coment	
\$ 788'. STA	GE 8: Cemented w/100	sks RFC - tagged cemen	t 🖲 718'. 🤅	STAGE 9:	
Cemented w/1 Redi-Mix - *	00 sks RFC - tagged ce	STAGE 11: Comented w/8	: Comented w	w/8 yds of -Wix - tagged	
cement @ 388	'. STAGE 12: Comente	d w/150 sks Class "C"	- brought co	sment to	
		est to 1200 psi - held	OK.		
8-18-78 Logging well 8-28-78 Drilling @ 8					
-					
18. I hereby certify that the forego	ling is true and correct	Arent	<u>en</u>		
SIGNED Anul	TITLE	Agent	DATE	8-30-78	
(This space or Federal r Sta	te office use	ACTING DISTRICT ENGINE	ER	SEP 1 1 1978	
APPROVED BY CONDITIONS OF APPROVAL,	IF ANY:	ACTING DISTRICT ENGINE ARTESIA, NEW MEXIC	DATE		
\mathcal{U}		MEXIC	20		

*See Instructions on Reverse Side