

RECEIVED

| | |
|------------------------|---|
| NO. OF COPIES RECEIVED | 3 |
| DISTRIBUTION | |
| SANTA FE | / |
| FILE | / |
| U.S.G.S. | |
| LAND OFFICE | |
| OPERATOR | / |

NEW MEXICO OIL CONSERVATION COMMISSION

O. C. C.
ARTEBIA, OFFICEForm C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

| | |
|--------------------------------|---|
| 5a. Indicate Type of Lease | |
| State <input type="checkbox"/> | Fee <input checked="" type="checkbox"/> |
| 5. State Oil & Gas Lease No. | |

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

| | | |
|---|--|---|
| 1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- | | 7. Unit Agreement Name |
| 2. Name of Operator Hanagan Petroleum Corporation ✓ | | 8. Farm or Lease Name Crusader Rabbit Com |
| 3. Address of Operator P.O. Box 1737 - Roswell, New Mexico 88201 | | 9. Well No. I |
| 4. Location of Well UNIT LETTER <u>C</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>West</u> LINE, SECTION <u>8</u> TOWNSHIP <u>19S</u> RANGE <u>26E</u> NMPM. | | 10. Field and Pool, or Wildcat <u>West Four Mile Draw</u> <u>Morrow</u> |
| 15. Elevation (Show whether DF, RT, GR, etc.) 3378 GR | | 12. County Eddy |

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
 TEMPORARILY ABANDON ☐
 PULL OR ALTER CASING ☐
 OTHER ☐

PLUG AND ABANDON ☐
 CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
 COMMENCE DRILLING OPNS. ☒
 CASING TEST AND CEMENT JOB ☒
 OTHER ☐
 ALTERING CASING ☐
 PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7/10/78 : Spud w/rotary tools 7:30 A.M. (Moranco drilling contractor)
 tD 370'-ran 9 jts. 13 3/8" 48#st&c surface casing (373') in
 17 1/2" hole set @ 370' cmt. Howco w/ 390 sx class "c"-2%CaCl,
 circ, 50 sx excess, Plugdown 1:00 A.M. - 7/11/78

7/11/78 : Drilled plug. 1:00 P.M. (WOC 12 hrs.) Press. up 600# 30 min., no
 press drop.

7/12/78 : TD 1300' - Ran 32 jts. 8-5/8" new 32#Lt&c & 24#stsc casing
 (1328') set @ 1300' cmt. Howco w/550sx Howco light 5#Gilsonite
 1/4# flocel 2% CaCl, +150 sx Class "C" 2% CaCl, Circ out 50 sx
 excess, plug down 1:15 A.M. 7/13/78. Drilled Plug @ 9:00 P.M.
 yellow jacket B.O.P. & 8-5/8" csq w/3000# 30 min., held.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Mr. SouthardTITLE AgentDATE 7/18/78APPROVED BY W.A. GussertTITLE SUPERVISOR, DISTRICT IIDATE JUL 20 1978

CONDITIONS OF APPROVAL, IF ANY: