

9/5F

Form 9-331  
Dec. 1973Form Approved.  
Budget Bureau No. 42-R1424UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR  
AMOCO PRODUCTION COMPANY

3. ADDRESS OF OPERATOR  
P. O. Box 68, Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980' FSLX 660' FWL, Unit L  
AT TOP PROD. INTERVAL: Sec. 34, T-18-S, R-31-E  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE  
LC-029392-b

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Greenwood Pre-Grayburg Unit

9. WELL NO.  
11

10. FIELD OR WILDCAT NAME  
Shugart Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
34-18-31

12. COUNTY OR PARISH  
Eddy

13. STATE  
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3629' RDB

## REQUEST FOR APPROVAL TO:

## SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☒

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) ☐

☐

☐

☐


☐

☐

☐

☐

☐



NOTE: Report results of multiple completion or zone change on Form 9-330.

OCT 12 8 0 AM '83  
RECEIVED  
BUREAU OF LAND MGMT  
ROSWELL DISTRICT

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Propose to increase gas production by reducing the water production as follows:  
Move in service unit and kill well with 2% KCL brine water. Release packer and pull along with tubing. Run in hole with cast iron bridge plug on Wireline set at 12,000' and cap with 35' cement using a dump bailer. Run in hole with 2-3/8" tubing with standard sand on bottom. Set tubing at 11,700' swab and place back on production.

0+4-B1M, R 1-Hou F. J. Nash, Rm 4.206 1-Hou R. E. Ogden Rm 21.150  
1-PJS 1-NMOCDA

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Peter W. Chester TITLE Ast. Amd. Analyst DATE 10-10-83

APPROVED (This space for Federal or State office use)

(Orig. Sgd.) PETER W. CHESTER

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

OCT 21 1983