

c/sf

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
RECEIVED BYSUNDRY NOTICES AND REPORTS
JUN 11 1986

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐ P&A2. NAME OF OPERATOR
Yates Petroleum Corporation3. ADDRESS OF OPERATOR
207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1980 FNL & 660 FEL, Sec. 35-19S-27E

AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☒RECEIVED
FEB 16 1982

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

5. LEASE

NM-02295

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Ruddy Trigg JV Federal

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Angell Ranch Atoka Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unit H, Sec. 35-T19S-R27E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3433' KB

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Well plugged and abandoned as per USGS instructions as follows:

Plug #1 - 10198-9846' w/25 sx Class C CaCl

Plug #2 - 8860-8500' w/25 sx Class C CaCl

Plug #3 - 3300-3000' w/35 sx Class C CaCl across 4 1/2" casing steel, P.V.C

Plug #4 - 2435-2250' w/35 sx Class C CaCl

Plug #5 - 15 sx Class C to surface.

Heavy mud placed between all plugs. Regulation abandonment marker will be installed. Surface will be restored in accordance with USGS-BLM requirements.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED James L. Goodwin TITLE Engineering Secty DATE 2-10-82

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE 6-9-86

CONDITIONS OF APPROVAL, IF ANY:

Post ID-2
6-13-86
PFA

