

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 4986

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

GULF OIL CORPORATION

3. ADDRESS OF OPERATOR

P. O. Box 670, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

2280' FNL & 660' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3391' GL

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Pacheco Federal Com

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Angell Ranch Morrow

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec 31, T-19S, R-28E

12. COUNTY OR PARISH 13. STATE

Eddy

New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

McVay Drilling Company Rig #4 spudded a 17-1/2" hole @ 2:30 P.M., 9-8-78. Reached TD of 17-1/2" hole (421') @ 10:30 P.M., 9-8-78. Ran 10 jts & 1 cut jt (406') of 13-3/8" 48# H-40 ST&C casing. Set @ 421'. Float collar @ 385.89'. Cemented with 450 sacks of Class "C" with 6% gel & 1/4# Flocele tailed in with 175 sacks of Class "C" Neat cement with 2% CaCl<sub>2</sub>. Cement circulated. Plug down @ 5:00 A.M., 9-9-78. WOC 18 hours.

Tested 13-3/8" casing to 500# for 30 minutes; held o.k.

Began drilling 12-1/4" hole @ 1:30 A.M., 9-10-78.

RECEIVED

SEP 12 1978

U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Area Engineer

DATE

09-11-78

(This space for Federal or State office use)

APPROVED BY

TITLE

ACTING DISTRICT ENGINEER

DATE

SEP 13 1978

CONDITIONS OF APPROVAL, IF ANY: