

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Oil Cons. Division  
FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1991

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Hanley Petroleum Inc.

3. Address and Telephone No.

415 W. Wall, Suite 1500, Midland, TX 79701 (915) 684-8051

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FSL & 2080 FWL of Section 31, T-19-S, R-31-E

NM 97136

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Adams Federal #1

9. API Well No.

30-015-22613

10. Field and Pool, or Exploratory Area

Hackberry Bone Spring

11. Country or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☒ Recompletion  
☒ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Hanley Petroleum Inc. plans to plug back and test the First Bone Spring Sand. A retrievable bridge plug will be set @ +/- 8700' to isolate the second Bone Spring Sand. Perforate the first Bone Spring w/ 2 bullets per foot from 7976-8010'. Acidize w/ 3000 gals of 7 1/2 % HCL and ball sealers. Swab and evaluate for frac treatment.

This work should commence 4/29/97.



14. I hereby certify that the foregoing is true and correct

Signed Greg Wilkins

Title Chief Engineer

Date 4/24/97

(This space for Federal or State office use)

(ORIG. SCD) DAVID R. GLASS

PETROLEUM ENGINEER

MAY 06 1997

Approved by \_\_\_\_\_  
Conditions of approval, if any: