		ELOGICAL SI		SUBMIT IN TRIP. (Other instructions verse side)	. TE -	D. LEASE DESIGNATION A	
						NM-7049 5 B. IF INDIAN, ALLOTTED	OR TRIBE NAME
JUI (Do not use th	NDKY NOII	CES AND RE	PORIS ON	WELLS			
	Use "APPLICA	TION FOR PERMIT-	-" for such proposa	a different reservoir.	•	N 31	-198n
1. 01L GAS		Dmy				. UNIT AGREEMENT NAM	ir.
WELL WELL 2. NAME OF OPERATOR	LA OTHER	Dry				<u> </u>	D.
	ompany 📿				1	3. FARM OR LEADE NAME	FICE
3. ADDRESS OF OPERAT						Langley-Feder	al
2000 Classe	n Bldg., 20	0 South 0	klahoma Cit	y, Oklahoma-7		1	
4. LOCATION OF WELL See also space 17 be	(Report location cle elow.)	early and in accordan	ice with any State	requirement	· · · · · · · · · · · · · · · · · · ·	0. FIELD AND POOL, OR	WILDCAT
At surface			R	EU		Wildcat 17	cha No
990' FNL &	1980'FWL		-	1 2 1975	3 1	1. SEC., T., R., M., OR BL SURVEY OR AREA	K. AND
				JAN 1 2 1979	. WEV		
14. PERMIT NO.		15. ELEVATIONS (Sho	w whether DF, RT, GR	JAN A teta) J. S. GEULUGUNA J. S. GEULUGUNA NEW M	EVICE 1	ec 4, T205, R2	23E 18. STATE
		4067.6' GI	R N	ARTESIA, NEW M	EVION		•
6.	Check Ap			AHILMIN	<u>.</u>		lew Mexico
	NOTICE OF INTENT			of Notice, Repor	t, or Oth	er Data	· •
]			£	SUBSEQUEN:	T BEPORT OF:	
TEST WATER SHUT-		ULL OR ALTER CASING		WATER SHUT-OFF		BEPAIRING WE	LL
FRACTURE TREAT Shoot or acidize	[]	ULTIPLE COMPLETE		FRACTURE TREATMENT		ALTERING CAS	ÍNG
REPAIR WELL		HANGE PLANS		SHOOTING OR ACIDIZII (Other)	NG	ABANDONMENT	• <u> X</u> _
(Other)				(NOTE : Report	results of	multiple completion on on Report and Log form	Well
 DESCRIBE PROPOSED (proposed work. I nent to this work.) 	OR COMPLETED OPER If well is direction	ATIONS (Clearly state ally drilled, give sub	all pertinent detai surface locations an	ils, and give pertinent nd measured and true	dates, inc vertical de	luding estimated date epths for all markers a	of starting any and zones perti-
						الم	
uall use duail	100 FN A VII	J OT 8430'.	NO Shows we	are encounter	ad 6.7.		1. tho
well was drill		+ -		ere encounter	eu pero	ow the Abo and	L'ALLE
well was drill owing cement p	plugs were s	set:				ow the Abo and	
well was drill owing cement p	olugs were s	set: 45 sks	s from 8076-	-8226'	ed per	DW THE ADD and	มายร้าวเวลี่ย เมืองว่าสี่ย เมืองว่าสี่ย
owing cement p	Jugs were s	set: 45 sks 45 sks 30 sks	s from 8076- s from 6351- s from 4805-	-8226' -6501' -4905'			กรรณิยาร์ เรื่องกลัยาร์
/8" casing was	s set at 280	set: 45 sks 45 sks 30 sks 0' and cement	5 from 8076 5 from 6351 5 from 4805 5 ed with 250	-8226' -6501' -4905') sks (lass "(
/8" casing was set at 1773' w	s set at 280 //800 sks ce	set: 45 sks 45 sks 30 sks 0' and cement ement. 4%" o	from 8076 from 6351 from 4805 ed with 250	-8226' -6501' -4905') sks Class "(set through ;	C" ceme	ent and 4% CaC	1. 8-5/8'
/8" casing was set at 1773' w Class "C" ceme	s set at 280 v/800 sks ce ent. The we	set: 45 sks 45 sks 30 sks 0' and cement ement. 4½" c all was perfo	s from 8076 s from 6351 s from 4805 ced with 250 casing was s prated in th	-8226' -6501' -4905') sks Class "(set through to be Abo from 4'	C" ceme the Abo	ent and 4% CaC o and cemented	1977 1977 1977 1977 1977 1977 1977 1977
/8" casing was set at 1773' w Class "C" ceme s. Abo was th	s set at 280 /800 sks ce ent. The we	set: 45 sks 45 sks 30 sks 0' and cement ement. 4½" c all was perfo 1 with 2500 c	s from 8076- s from 6351- s from 4805- ced with 250 casing was s prated in the wals. 15% H0	-8226' -6501' -4905') sks Class "(set through t he Abo from 4!) acid and re	C" ceme the Abo 554-460	ent and 4% CaC o and cemented 04 with a tot	1. 8-5/8' with 150
/8" casing was set at 1773' w Class "C" ceme s. Abo was th ed water and 5	s set at 280 /800 sks ce ent. The we nen acidized	set: 45 sks 45 sks 30 sks 0' and cement ement. 4½" c 211 was perfo 1 with 2500 g sand. The w	s from 8076 s from 6351 s from 4805 ced with 250 casing was s prated in th gals. 15% HO yell was tes	-8226' -6501' -4905') sks Class "(set through t ne Abo from 4 Cl acid and rested on the p	C" ceme the Abo 554-460 etreate	ent and 4% CaC o and cemented 04! with a tot ed with 60,000	1. 8-5/8' with 150 gals.
/8" casing was set at 1773' w Class "C" ceme s. Abo was th ed water and 5 was not comme	s set at 280 v/800 sks ce ent. The we ien acidized 50,000 lbs. ercial and a	set: 45 sks 45 sks 30 sks 0' and cement ement. 4½" c all was perfo 1 with 2500 g sand. The wapproval to p	s from 8076 s from 6351 s from 4805 ced with 250 casing was s prated in th gals. 15% HO well was tes	-8226' -6501' -4905' D sks Class "(set through the Abo from 4 Cl acid and re sted on the pu	C" ceme the Abo 554-460 etreate ump for	ent and 4% CaC o and cemented 04! with a tot ed with 60,000 c 2 BOPD and 1 n the USCS	1. 8-5/8' with 150 al of 50 gals. 5 MCFGPD.
/8" casing was set at 1773' w Class "C" ceme s. Abo was th ed water and 5 was not comme plugged commen	s set at 280 v/800 sks ce ent. The we fon acidized 50,000 lbs. ercial and a acing on 12-	45 sks 45 sks 30 sks 30 sks 1 and cement ement. 4½" c all was perfo 1 with 2500 g sand. The w approval to p 29-78 and co	s from 8076 from 6351 from 4805- ced with 250 casing was so prated in the pals. 15% HO well was tes olug the well ompleted on	-8226' -6501' -4905') sks Class "(set through t te Abo from 4 Cl acid and re ted on the pu t was receive 1-3-79 The	C" ceme the Abc 554-460 etreate ump for ed fron well w	ent and 4% CaC o and cemented 04! with a tot ed with 60,000 2 BOPD and 1 n the USGS. T	1. 8-5/8' with 150 al of 50 gals. 5 MCFGPD. he well
/8" casing was set at 1773' w Class "C" ceme s. Abo was th ed water and 5 was not comme plugged commen owing manner: -4500'. Casin	s set at 280 (/800 sks ce ent. The we ben acidized (0,000 lbs. ercial and a locing on 12- 4½" casing og was shot	set: 45 sks 30 sks 30 sks 30 sks 30 sks 30 sks 30 sks 45 sks 30 s	s from 8076 from 6351 from 4805 at with 250 asing was so rated in the als. 15% HO well was tes olug the well well was tes olug the well with salt of and a 35 so	-8226' -6501' -4905' D sks Class "(Set through f the Abo from 4! Cl acid and re sted on the pu the steeive 1 was receive 1-3-79. The gel mud and a	C" ceme the Abc 554-460 etreate ump for ed from well v 25 sk	ent and 4% CaC o and cemented O4' with a tot ed with 60,000 2 BOPD and 1 n the USGS. T vas plugged in plug was set at the top of	1. 8-5/8' with 150 al of 50 gals. 5 MCFGPD. he well the from
/8" casing was set at 1773' w Class "C" ceme s. Abo was th ed water and 5 was not commen plugged commen plugged commen owing manner: -4500'. Casin casing. The 4	s set at 280 (/800 sks ce ent. The we ben acidized 50,000 lbs. ercial and a locing on 12- 4½" casing 12 was shot 12" casing w	set: 45 sks 30 sks	s from 8076 s from 6351 s from 4805 ced with 250 casing was s prated in the gals. 15% HO well was tes olug the well well was tes olug the well well salt of and a 35 s 1860' when	-8226' -6501' -4905' D sks Class "(set through the set through the l acid and re ted on the pu ted on the pu ted on the pu ted and a sk plug was sp te a 35 sk cer	C" ceme the Abo 554-460 etreate ump for ed fron well v 25 sk potted	ent and 4% CaC o and cemented 04' with a tot ed with 60,000 2 BOPD and 1 n the USGS. T vas plugged in plug was set at the top of	1. 8-5/8' with 150 gals. 5 MCFGPD. he well the from the om 1860'
/8" casing was set at 1773' w Class "C" ceme s. Abo was th ed water and 5 was not comme plugged commen owing manner: -4500'. Casin casing. The 4 oproximately 1	s set at 280 (/800 sks ce ent. The we nen acidized 50,000 lbs. ercial and a cing on 12- 4½" casing 1½" casing w .660'. The	set: 45 sks 30 sks 30 sks b' and cement ement. 4½" c all was perfo all with 2500 g sand. The w approval to p 29-78 and co y was loaded off at 3950' was pulled to remainder of	s from 8076 s from 6351 s from 4805 ced with 250 casing was s prated in the yals. 15% HO yell was tes plug the well with salt of and a 35 s 1860' wher the 4%" ca	-8226' -6501' -4905' D sks Class "(set through the set through the l acid and re ted on the pu l acid and re ted on the pu l was receive 1-3-79. The gel mud and a sk plug was spore a 35 sk cen	C" ceme the Abo 554-460 etreate ump for ed from well w 25 sk potted nent pl	ent and 4% CaC o and cemented 04' with a tot ed with 60,000 2 BOPD and 1 n the USGS. T vas plugged in plug was set at the top of ug was run fr	1. 8-5/8' with 150 gals. 5 MCFGPD. he well the from the om 1860' ead takon
/8" casing was set at 1773' w Class "C" ceme s. Abo was th ed water and 5 was not comme plugged commen bwing manner: -4500'. Casin casing. The 4 pproximately 1 and a 10 sk pl	s set at 280 (/800 sks ce ent. The we ien acidized 50,000 lbs. ercial and a acing on 12- 4½" casing ug was shot 1½" casing w 560'. The ug was spot	set: 45 sks 30 sks 30 sks b' and cement ement. 4½" c all was perfo all with 2500 g sand. The w approval to p 29-78 and co y was loaded off at 3950' was pulled to remainder of	s from 8076 s from 6351 s from 4805 ced with 250 casing was s prated in the yals. 15% HO yell was tes plug the well with salt of and a 35 s 1860' wher the 4%" ca	-8226' -6501' -4905' D sks Class "(set through the set through the l acid and re ted on the pu l acid and re ted on the pu l was receive 1-3-79. The gel mud and a sk plug was spore a 35 sk cen	C" ceme the Abo 554-460 etreate ump for ed from well w 25 sk potted nent pl	ent and 4% CaC o and cemented 04' with a tot ed with 60,000 2 BOPD and 1 n the USGS. T vas plugged in plug was set at the top of ug was run fr	1. 8-5/8' with 150 gals. 5 MCFGPD. he well the from the om 1860' ead takon
/8" casing was set at 1773' w Class "C" ceme s. Abo was th ed water and 5 was not comme plugged commen pwing manner: -4500'. Casin casing. The 4 pproximately 1 and a 10 sk pl	s set at 280 (/800 sks ce ent. The we ien acidized 50,000 lbs. ercial and a acing on 12- 4½" casing ug was shot 1½" casing w 560'. The ug was spot	set: 45 sks 30 sks 30 sks b' and cement ement. 4½" c all was perfo all with 2500 g sand. The w approval to p 29-78 and co y was loaded off at 3950' was pulled to remainder of	s from 8076 s from 6351 s from 4805 ced with 250 casing was s prated in the yals. 15% HO yell was tes plug the well with salt of and a 35 s 1860' wher the 4%" ca	-8226' -6501' -4905' D sks Class "(set through the set through the l acid and re ted on the pu l acid and re ted on the pu l was receive 1-3-79. The gel mud and a sk plug was spore a 35 sk cen	C" ceme the Abo 554-460 etreate ump for ed from well w 25 sk potted nent pl	ent and 4% CaC o and cemented 04' with a tot ed with 60,000 2 BOPD and 1 n the USGS. T vas plugged in plug was set at the top of ug was run fr	1. 8-5/8' with 150 gals. 5 MCFGPD. he well the from the om 1860' ead takon
/8" casing was set at 1773' w Class "C" ceme s. Abo was th ed water and 5 was not comme plugged commen owing manner:	s set at 280 (/800 sks ce ent. The we ien acidized 50,000 lbs. ercial and a acing on 12- 4½" casing ug was shot 1½" casing w 560'. The ug was spot	set: 45 sks 30 sks 30 sks b' and cement ement. 4½" c all was perfo all with 2500 g sand. The w approval to p 29-78 and co y was loaded off at 3950' was pulled to remainder of	s from 8076 s from 6351 s from 4805 ced with 250 casing was s prated in the yals. 15% HO yell was tes plug the well with salt of and a 35 s 1860' wher the 4%" ca	-8226' -6501' -4905' D sks Class "(set through the set through the l acid and re ted on the pu l acid and re ted on the pu l was receive 1-3-79. The gel mud and a sk plug was spore a 35 sk cen	C" ceme the Abo 554-460 etreate ump for ed from well w 25 sk potted nent pl	ent and 4% CaC o and cemented 04' with a tot ed with 60,000 2 BOPD and 1 n the USGS. T vas plugged in plug was set at the top of ug was run fr	1. 8-5/8' with 150 gals. 5 MCFGPD. he well the from the om 1860' ead takon
/8" casing was set at 1773' w Class "C" ceme s. Abo was th ed water and 5 was not comme plugged commen bwing manner: -4500'. Casin casing. The 4 pproximately 1 and a 10 sk pl	s set at 280 (/800 sks ce ent. The we ien acidized 50,000 lbs. ercial and a acing on 12- 4½" casing ug was shot 1½" casing w 560'. The ug was spot	set: 45 sks 30 sks 30 sks b' and cement ement. 4½" c all was perfo all with 2500 g sand. The w approval to p 29-78 and co y was loaded off at 3950' was pulled to remainder of	s from 8076 s from 6351 s from 4805 ced with 250 casing was s prated in the yals. 15% HO yell was tes plug the well with salt of and a 35 s 1860' wher the 4%" ca	-8226' -6501' -4905' D sks Class "(set through the set through the l acid and re ted on the pu l acid and re ted on the pu l was receive 1-3-79. The gel mud and a sk plug was spore a 35 sk cen	C" ceme the Abo 554-460 etreate ump for ed from well w 25 sk potted nent pl	ent and 4% CaC o and cemented 04' with a tot ed with 60,000 2 BOPD and 1 n the USGS. T vas plugged in plug was set at the top of ug was run fr	1. 8-5/8' with 150 gals. 5 MCFGPD. he well the from the om 1860' ead takon
/8" casing was set at 1773' w Class "C" ceme s. Abo was th ed water and 5 was not comme plugged commen bwing manner: -4500'. Casin casing. The 4 pproximately 1 and a 10 sk pl	s set at 280 v/800 sks ce ent. The we ent acidized 50,000 lbs. ercial and a cing on 12- 4½" casing ug was shot ½" casing w .660'. The ug was spot the hole.	45 sks 45 sks 30 sks 30 sks and cement ement. 4½" c all was perfor with 2500 g sand. The was pproval to p 29-78 and co g was loaded off at 3950' was pulled to remainder of ted in the t	s from 8076 s from 6351 s from 4805 ced with 250 casing was s prated in the yals. 15% HO yell was tes plug the well with salt of and a 35 s 1860' wher the 4%" ca	-8226' -6501' -4905' D sks Class "(set through the set through the l acid and re ted on the pu l acid and re ted on the pu l was receive 1-3-79. The gel mud and a sk plug was spore a 35 sk cen	C" ceme the Abo 554-460 etreate ump for ed from well w 25 sk potted nent pl	ent and 4% CaC o and cemented 04' with a tot ed with 60,000 2 BOPD and 1 n the USGS. T vas plugged in plug was set at the top of ug was run fr	1. 8-5/8' with 150 gals. 5 MCFGPD. he well the from the om 1860' ead takon
/8" casing was set at 1773' w Class "C" ceme s. Abo was th ed water and 5 was not comme plugged commen owing manner: -4500'. Casin casing. The 4 oproximately 1 and a 10 sk pl er placed on t	s set at 280 (1800 sks ce ent. The we ben acidized 50,000 lbs. ercial and a acing on 12- 4½" casing was shot 1½" casing w 660'. The ug was spot the hole.	45 sks 45 sks 30 sks 30 sks b' and cement ement. 4½" c all was perfor with 2500 g sand. The w approval to p 29-78 and co y was loaded off at 3950' was pulled to remainder of ted in the t	s from 8076 s from 6351 s from 4805 ced with 250 sasing was s prated in the jals. 15% HO well was tes oug the well with salt of and a 35 s 1860' when the 4½" ca op of the 8	-8226' -6501' -4905' D sks Class "(set through the ne Abo from 4! Cl acid and re sted on the pu l acid and re sted on the pu l was receive 1-3-79. The gel mud and a sk plug was sp re a 35 sk cen sing was ther 3-5/8" casing	C" ceme the Abo 554-460 etreate ump for ed from well w 25 sk potted nent pl	ent and 4% CaC o and cemented 04' with a tot ed with 60,000 c 2 BOPD and 1 n the USGS. T vas plugged in plug was set at the top of lug was run fr ed, the well h regulation dr	1. 8-5/8' with 150 al of 50 gals. 5 MCFGPD. he well the from the om 1860' ead taken y hole
/8" casing was set at 1773' w Class "C" ceme s. Abo was th ed water and 5 was not commen plugged commen owing manner: -4500'. Casin casing. The 4 oproximately 1 and a 10 sk pl er placed on t	s set at 280 (/800 sks ce ent. The we ben acidized 50,000 lbs. ercial and a locing on 12- 4½" casing 1½" casing w 1½" casing w	45 sks 45 sks 30 sks 30 sks b' and cement ement. 4½" c all was perfor with 2500 c sand. The was poroval to p 29-78 and co y was loaded off at 3950' was pulled to remainder of ted in the t	s from 8076 s from 6351 s from 4805 ced with 250 casing was s prated in the yals. 15% HO yell was tes plug the well with salt of and a 35 s 1860' wher the 4%" ca	-8226' -6501' -4905' D sks Class "(set through the ne Abo from 4! Cl acid and re sted on the pu l acid and re sted on the pu l was receive 1-3-79. The gel mud and a sk plug was sp re a 35 sk cen sing was ther 3-5/8" casing	C" ceme the Abo 554-460 etreate ump for ed from well w 25 sk potted nent pl	ent and 4% CaC o and cemented 04' with a tot ed with 60,000 2 BOPD and 1 n the USGS. T vas plugged in plug was set at the top of ug was run fr	1. 8-5/8' with 150 al of 50 gals. 5 MCFGPD. he well the from the om 1860' ead taken y hole
/8" casing was set at 1773' w Class "C" ceme s. Abo was th ed water and 5 was not comme plugged commen owing manner: -4500'. Casin casing. The 4 oproximately 1 and a 10 sk pl er placed on t	s set at 280 (/800 sks ce ent. The we ben acidized 50,000 lbs. ercial and a cing on 12- 4½" casing g was shot ½" casing w 660'. The ug was spot he hole. the foregoing is t <u>Vater, ir</u> eral or State office	45 sks 45 sks 30 sks 30 sks b' and cement ement. 4½" c all was perfor with 2500 c sand. The was perfored to p 29-78 and co yeas loaded off at 3950' was pulled to remainder of ted in the t	s from 8076 s from 6351 s from 4805 ced with 250 casing was s prated in the gals. 15% HO well was tes oug the well ompleted on with salt of and a 35 s 1860' when the 4½" cas op of the 8 cop of the 8	-8226' -6501' -4905' D sks Class "(set through f the Abo from 4! Cl acid and re ted on the pu take on the pu take on the pu take of the pu t	C" ceme the Abo 554-460 etreate ump for ed from well v 25 sk potted nent pl n pulle and a	ent and 4% CaC o and cemented 04' with a tot ed with 60,000 2 BOPD and 1 n the USGS. T vas plugged in plug was set at the top of lug was run fr ed, the well h regulation dr	1. 8-5/8" with 150 al of 50 gals. 5 MCFGPD. he well the from the om 1860' ead taken y hole 9
/8" casing was set at 1773' w Class "C" ceme s. Abo was th ed water and 5 was not comme plugged commen owing manner: -4500'. Casin casing. The 4 oproximately 1 and a 10 sk pl er placed on t B. I hereby certify that signed for Fede (This space for Fede	s set at 280 (1800 sks ce ent. The we ben acidized 50,000 lbs. ercial and a acing on 12- 4½" casing was shot ½" casing w 660'. The ug was spot the hole. the foregoing is the state office 3. July 1155	45 sks 45 sks 30 sks 30 sks b' and cement ement. 4½" c all was perfor d with 2500 g sand. The w approval to p 29-78 and co g was loaded off at 3950' was pulled to remainder of ted in the t	s from 8076 s from 6351 s from 4805 ced with 250 casing was s prated in the gals. 15% HO well was tes oug the well ompleted on with salt of and a 35 s 1860' when the 4½" cas op of the 8 cop of the 8	-8226' -6501' -4905' D sks Class "(set through the ne Abo from 4! Cl acid and re sted on the pu l acid and re sted on the pu l was receive 1-3-79. The gel mud and a sk plug was sp re a 35 sk cen sing was ther 3-5/8" casing	C" ceme the Abo 554-460 etreate ump for ed from well v 25 sk potted nent pl n pulle and a	ent and 4% CaC b and cemented b4' with a tot ed with $60,000$ c 2 BOPD and 1 in the USGS. T vas plugged in plug was set at the top of lug was run fr ed, the well h regulation dr DATE <u>1-10-7</u>	<pre>1. 8-5/8" with 150 gals. 5 MCFGPD. he well the from the om 1860' ead taken y.hole 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9</pre>
/8" casing was set at 1773' w Class "C" ceme s. Abo was th ed water and 5 was not comme plugged commen owing manner: -4500'. Casin casing. The 4 oproximately 1 and a 10 sk pl er placed on t	s set at 280 (1800 sks ce ent. The we ben acidized 50,000 lbs. ercial and a acing on 12- 4½" casing was shot ½" casing w 660'. The ug was spot the hole. the foregoing is the state office 3. July 1155	45 sks 45 sks 30 sks 30 sks b' and cement ement. 4½" c all was perfor d with 2500 g sand. The w approval to p 29-78 and co g was loaded off at 3950' was pulled to remainder of ted in the t	s from 8076 s from 6351 s from 4805 ced with 250 casing was s prated in the gals. 15% HO vell was tes oug the well ompleted on with salt of and a 35 s 1860' when the 4½" cas op of the 8 so of the 8	-8226' -6501' -4905' D sks Class "(set through f the Abo from 4! Cl acid and re ted on the pu take on the pu take on the pu take of the pu t	C" ceme the Abo 554-460 etreate ump for ed from well v 25 sk potted nent pl n pulle and a	ent and 4% CaC b and cemented b4' with a tot ed with $60,000$ c 2 BOPD and 1 in the USGS. T vas plugged in plug was set at the top of lug was run fr ed, the well h regulation dr DATE <u>1-10-7</u>	1. 8-5/8" with 150 al of 50 gals. 5 MCFGPD. he well the from the om 1860' ead taken y hole 9
/8" casing was set at 1773' w Class "C" ceme s. Abo was th ed water and 5 was not comme olugged commen owing manner: -4500'. Casin casing. The 4 oproximately 1 and a 10 sk pl er placed on t B. I hereby certify that signed for Fede (This space for Fede	s set at 280 (1800 sks ce ent. The we ben acidized 50,000 lbs. ercial and a acing on 12- 4½" casing was shot ½" casing w 660'. The ug was spot the hole. the foregoing is the state office 3. July 1155	45 sks 45 sks 30 sks 30 sks b' and cement ement. 4½" c all was perfor d with 2500 g sand. The w approval to p 29-78 and co g was loaded off at 3950' was pulled to remainder of ted in the t	s from 8076 s from 6351 s from 4805 ced with 250 casing was s prated in the gals. 15% HO vell was tes oug the well ompleted on with salt of and a 35 s 1860' when the 4½" cas op of the 8 so of the 8	-8226' -6501' -4905' D sks Class "(set through f the Abo from 4! Cl acid and re ted on the pu take on the pu take on the pu take of the pu t	C" ceme the Abo 554-460 etreate ump for ed from well v 25 sk potted nent pl n pulle and a	ent and 4% CaC b and cemented b4' with a tot ed with $60,000$ c 2 BOPD and 1 in the USGS. T vas plugged in plug was set at the top of lug was run fr ed, the well h regulation dr DATE <u>1-10-7</u>	1. 8-5/8' with 150 gals. 5 MCFGPD. he well the from the om 1860' ead taken y hole 9 9

THE REAL	 	
ted, on Fed- to applicable th regard to Consult local State offices. nt significant between and date well site		
ted, c o apy h rey Jonsu State betwe late w		n an
ndica y wit ffce. ts. (ts. (ilow, and d		
d, as i pursu lucular lucular state of iremen eral an with r well; well;	· · ·	
restain well operations, and reports of such operations when completed, as indicated, and, if approved or accepted by any State, on all lands in such State, pursuant to a the use of this form and the number of copies to be submitted, particularly with r will be issued by, or may be obtained from, the local Federal and/or State office. ral or Indian land should be described in accordance with Federal requirements. Cons ment should include such special information as is required by local Federal and/or Stat nament; data on any former or present productive zones, or other zones with present si) and method of placement of cement plugs; mud or other material placed below, betw lied and the depth to top of any left in the hole; method of closing top of well; and date anwewremine office:		
s when ds in submit Federal ith Fed ith Fed ift of clos		
well operations, and reports of such operations approved or accepted by any State, on all land e of this form and the number of copies to be is sued by, or may be obtained from, the local F Indian land should be described in accordance wi should include such special information as is requi ; data on any former or present productive zones method of placement of cement plugs; mud or of d the depth to top of any left in the hole; method intime orice: 181-0-88228		
th ope e, on copie n, the accord duction as set. n ble;	an an an an an an Arthrean Arthrean Ann an Arth Ann an Ann an	 A second s
I from r of l in a l in a rmati t pro t plug	1 1	
any any cribed cribed cribed nesen nesen nesen left in		n an an Araba an Arab Araba an Araba an Arab
e des e des pecla t of c any		e e e e e e e e e e e e e e e e e e e
such s forme cement top of +685229		
id sho lude s any f plac th to t tiss-o-	en e	
ain well oper- i, if approved a use of this i be issued by or Indian lan or Indian lan or should inc ent; data on and method of a and the dept evremence of pre-		- Cheller Alter and Alter
certain wel and, if app it the use of r will be iss eral or Indi eral or Indi onment shou lonment; da m) and met ulled and th vertimet		ting and the second s Second second
and		
Federa Bandonn bandon ootton) Ing pull		
uns on Federal or Indian land should look abandonment should include such the abandonment; data on any forme and bottoin) and method of placement tubing pulled and the depth to top of ment.		and and the second s Second second s Second second
Ports of abandonn sa for the abandon (top and bottom) lner or tubing pull andonment. us.coverw		
nus, notations of a bandonn ent reports of a bandonn easons for the abandon spths (top and bottom) ing, liner or tubing pull he abandonment. us covers		
sequent reports of abandonn Inde reasons for the abandon se; depths (top and bottom) y casing, liner or tubing pull I of the abandonment. U.S. GOVENN		
us. In subsequent reports of abandonn d include reasons for the abandon nerwise; depths (top and bottom) of any casing, liner or tubing pull proval of the abandonment. U.S. GOVEN		
State requirements, locations on Feders uctions. Fell and subsequent reports of abandon should include reasons for the abandon or otherwise; depths (top and bottom) urting of any casing, liner or tubing pull to approval of the abandonment.		
and practices, entirer are snown below or w cable State requirements, locations on Feders instructions. In a well and subsequent reports of abandon ports should include reasons for the abandon ports should include reasons for the abandon ports should include reasons for the abandon ports approval of the abandonment. Ming to approval of the abandonment.		
applicable State requirements, locations on Federe ecific instructions. andon a well and subsequent reports of abandon nd reports should include reasons for the abandon by cement or otherwise; depths (top and bottom) ethod of parting of any casing, liner or tubing pull on looking to approval of the abandonment. Us coverw		
e no applicable State requirements, locations on Federe or specific instructions. to abandon a well and subsequent reports of abandon asis and reports should include reasons for the abandon i off by cement or otherwise; depths (top and bottom) ze, method of parting of any casing, liner or tubing pull pection looking to approval of the abandonment. us.coven		
The are no applicable state requirements, locations on rederations filtee for specific instructions. ince for specific instructions. solutions and reports should include reasons for the abandon proposals and reports should include reasons for the abandon scaled off by cement or otherwise; depths (top and bottom) at, size, method of parting of any casing, liner or tubing pull al inspection looking to approval of the abandonment. Us covers		
r regional procedures and practices, either are shown below or w If there are no applicable State requirements, locations on Feders aral office for specific instructions. Proposals to abandon a well and subsequent reports of abandon uch proposals and reports should include reasons for the abandon s not sealed off by cement or otherwise; depths (top and bottom) amount, size, method of parting of any casing, liner or tubing pull or final inspection looking to approval of the abandonment.		
able Federal law and regulations, irry special instructions concerning ractices, either are shown below or tate requirements, locations on Fede stions. It and subsequent reports of abandon hould include reasons for the abando hould include reasons for the abando hould any casing, liner or tubing pu ting of any casing, liner or tubing pu sove		