

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Mesa Pk. Co.</i>		Lease <i>Gardner State</i>		Well # <i>1</i>	
Location of Well	Unit <i>K</i> <i>1980S+W</i>	Section <i>8</i>	Township <i>19</i>	Range <i>23</i>	County <i>Eddy</i>
Drilling Contractor	<i>Cactus Drilling #53</i>		Type of Equipment <i>Rotary to start 10-5-78</i>		
<i>Jim Wooten Company man</i> <u>APPROVED CASING PROGRAM</u>					
* <i>Witness</i>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>1 7/2</i>	<i>13 3/8"</i>	<i>48</i>		<i>225</i>	<i>400 cu.</i>
* <i>1 1/4</i>	<i>8 5/8"</i>	<i>24</i>		<i>1750</i>	<i>1000 "</i>
<i>8 7/8"</i>	<i>4 1/2"</i>	<i>10.5+11.6</i>		<i>7900</i>	<i>1200 cu.</i>
Casing Data:					
<i>Inter.</i>					
Surface joints of <i>8 5/8</i> inch <i>24</i> # Grade <i>K-55</i>					
(Approved) (Rejected)					
Inspected by <i>M.S.</i> date <i>10/17/78</i>					
Cementing Program					
Size of hole <i>11"</i> Size of Casing <i>8 5/8</i> Sacks cement required					
Type of Shoe used <i>Texas Pat</i> Float collar used <i>Insert</i> Btm 3 jts welded <i>yes</i>					
TD of hole <i>1697</i> Set <i>1697</i> Feet of <i>8 5/8</i> Inch <i>24</i> # Grade <i>K-55</i>					
New and csg. @ <i>1697</i> with <i>575</i> sacks neat cement around shoe					
+ <i>sax</i> additives					
Plug down @ <i>3:00</i> (PM) (PM) Date <i>10-28-78</i>					
Cement circulated <i>yes</i> No. of Sacks <i>45</i>					
Cemented by <i>Halliburton</i> Witnessed by <i>B.W. Weender</i>					
Temp. Survey ran @ (AM) (PM) Date top cement @					
Casing test @ (AM) (PM) Date					
Method Used Witnessed by					
Checked for shut off @ (AM) (PM) Date					
Method used Witnessed by					
Remarks:					