



Peabody Vann

Engineered Oil and Gas Well Completions

VANNSYSTEM PERFORATING INSTALLATION

FEB 28 1979

O.C.C.

RECEIVED

FILING NO.

COMPANY: Atlantic Richfield Company

WELL: STATE "CB" COM. #1

FIELD: WINCHESTER

COUNTY: EDDY

STATE: NEW MEXICO

LOCATION: 660' FSI & 1980' FTI

OTHER SERVICES:

SEC. 29 TWP. 19-S RGE. 20-E

PERMANENT DATUM: G.L. ELEV. 3382'

LOG MEASURED FROM: K.B. 18' FT. ABOVE PERM. DATUM

DRILLING MEASURED FROM: K.B.

ELEV. K.B. 3400'

D.F. -

G.L. 3382'

DATE: 1/26/79

RUN NO. 1

TYPE LOG: VANNSYSTEM PERFORATING ASSEMBLY

DEPTH-DRILLER

DEPTH-LOGGER

BOTTOM LOGGED INTERVAL

TOP LOGGED INTERVAL

TYPE FLUID IN HOLE

SALINITY, PPM CL

DENSITY

LEVEL

MAX. REC. TEMP. DEG. F.

OPERATING RIG TIME

RECORDED BY: MIKE ALLEN

WITNESSED BY: MR. ARNING

RUN

NO.

BIT

FROM

TO

SIZE

WGT.

FROM

TO

BORE-HOLE RECORD

CASING RECORD

SURFACE

6.09'

2 3/8" EUE 8rd C-75 Tubing Joint

2 3/8" EUE 8rd C-75 Landing Sub

2 3/8" EUE 8rd C-75 Tubing String
349 Joints

4 1/2" 11.6# Casing String

2 3/8" EUE 8rd C-75 Locator Sub

KEY LOCATOR COLLAR W/RA MARKER

2 3/8" EUE 8rd C-75 Tubing Joint

3 3/4" X 2 3/8" Baker "EL" On/Off Tool W/1.81" Profile

2 3/8" EUE 8rd C-75 Spacer Sub

2 3/8" EUE 8rd N-80 6" Nipple (W/Sand Shield)

43 A Baker Lok-Set Packer

Strapped Distance from TOP SHOT
59.28' to KEY LOCATOR COLLAR

VANNTAGE PACKER ACTUATED VENT ASSEMBLY, SN:1010-2-B

2 3/8" EUE 8rd C-75 Spacer Sub

2 3/8" EUE 8rd C-75 Handling Sub

2 3/8" EUE 8rd No-Go Safety Nipple W/1.50" I.D.

VANNTAGE MECHANICAL FIRING HEAD, SN: F669

TOP SHOT

3 3/8" X 3 3/8" O.D. Steel Carrier Gun
4' Loaded 2 JSF = 3--1.50" Dia. Holes

BOTTOM SHOT

3 3/8" O.D. Steel Bull Plug

Rathole

BBTD

108.30'

11,140.00'

11,031.70'

11,029.00'

4.00'

1.55'

11,023.45'

11,022.90'

4.08'

11,018.22'

6.00'

11,012.32'

2.26'

11,010.56'

.50'

11,007.36'

2.14'

10,999.12'

1.65'

10,997.47'

31.75'

10,965.72'

5.95'

10,959.77'

