

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Morris R. Cantrell</i>		Lease <i>Rios Siete</i>		Well # <i>1</i>	
Location of Well	Unit <i>19805 2310e</i>	Section <i>11</i>	Township <i>20</i>	Range <i>25</i>	County <i>Eddy</i>
Drilling Contractor	<i>Insurance #9</i>		Type of Equipment <i>Rotary to start 11-8-78</i>		
Company man <i>Jimmy Reynolds</i> <i>* Witness</i> APPROVED CASING PROGRAM					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>17 1/2"</i>	<i>13 3/8"</i>	<i>48</i>		<i>300</i>	<i>325 circ.</i>
<i>12 1/4"</i>	<i>8 5/8"</i>	<i>32</i>		<i>1500</i>	<i>580 "</i>
<i>7 7/8"</i>	<i>5 1/2"</i>	<i>17</i>		<i>9900</i>	<i>420</i>
Casing Data:					
<i>Inter.</i>					
<i>Surface</i> joints of <i>8 5/8</i> inch <i>24</i> # Grade <i>J-55</i>					
(Approved) (Rejected)					
Inspected by <i>M.S.</i> date <i>11/15/78</i>					
Cementing Program					
Size of hole <i>12 1/4</i> Size of Casing <i>8 5/8</i> Sacks cement required					
Type of Shoe used <i>guide</i> Float collar used <i>yes</i> Btm 3 jts welded <i>yes</i>					
TD of hole <i>1500'</i> Set <i>1500'</i> Feet of <i>8 5/8</i> Inch <i>24</i> # Grade <i>J-55</i>					
New-used csg. @ <i>1500'</i> with <i>2002 1/2</i> sacks neat cement around shoe					
+ <i>150</i> sax <i>thin set</i> additives <i>5# gelsolve 1/4# Dure</i>					
Plug down @ <i>7:30</i> (AM) (PM) Date <i>11/17/78</i>					
Cement circulated <i>yes</i> No. of Sacks <i>65</i>					
Cemented by <i>Halliburton</i> Witnessed by <i>Mike Stuppfield</i>					
Temp. Survey ran @ (AM) (PM) Date top cement @					
Casing test @ (AM) (PM) Date					
Method Used Witnessed by					
Checked for shut off @ (AM) (PM) Date					
Method used Witnessed by					
Remarks: <i>+ 400 Hall, Dite 5# salt - 1/2# flocc</i>					
<i>4 baskets @ 824'-736'-600'-467'</i>					
<i>3 centralizers @ 1450'-1350'-1250'</i>					
<i>last circ @ 550' int required</i>					
<i>Last dry break @ 760'</i>					