

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

RECEIVED

NEW MEXICO OIL CONSERVATION COMMISSION

NOV 21 1978

O. C. C.  
ARTESIA, OFFICE

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No. ---
7. Unit Agreement Name ---
8. Farm or Lease Name Rios Siete
9. Well No. 1
10. Field and Pool, or Wildcat Morrow Wildcat
12. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- 2. Name of Operator Morris R. Antweil ✓ 3. Address of Operator Box 2010, Hobbs, N. M. 88240 4. Location of Well UNIT LETTER J 1980 South 2310 THE East 11 LINE, SECTION 20-S RANGE 25-E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3366' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 12-1/4" hole to 1500'. Ran and cemented 8-5/8" 32# J-55 casing @ 1500' with 150 sx. Thixset cement, 400sx Halliburton lite cement containing 5#/sx salt and 1/2#/sx Flocele, and 200 sx. Class "C" cement containing 2% CaCl<sub>2</sub>. Plug down @ 7:30 AM 17 Nov 1978. Circulated approximately 65 sx. cement. Cement in annulus fell back. Filled annulus with 3 yards ready-mix. WOC 24 hrs. Tested casing with 2000 psi - 30 mins - OK. Drilled out w/7-7/8" bit.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Rm Williams TITLE Agent DATE 20 Nov. 1978

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE NOV 22 1978

CONDITIONS OF APPROVAL, IF ANY: