

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

RECEIVED

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
L-6287

SUNDRY NOTICES AND REPORTS ON WELLS DEC 13 1978
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL <input type="checkbox"/> GAS <input checked="" type="checkbox"/> OTHER- 2. Name of Operator Yates Petroleum Corporation ✓ 3. Address of Operator 207 South 4th Street - Artesia, NM 88210 4. Location of Well UNIT LETTER G 1980 FEET FROM THE North LINE AND 1980 FEET FROM THE East LINE, SECTION 12 TOWNSHIP 19S RANGE 24E NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 3604' GR	6. O.C.C. ARTESIA, OFFICE 7. Unit Agreement Name 8. Farm or Lease Name Irish Hill JE St. Com 9. Well No. 1 10. Field and Pool, or Wildcat Und, Boyd Morrow 12. County Eddy
--	--

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐
PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIATION WORK ☐
COMMENCE DRILLING OPNS. ☒
CASING TEST AND CEMENT JOB ☒
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1503.
Spudded a 17½" hole at 9:00 AM 12-3-78. TD 404' - Ran 11 jts of 13-3/8" 48# K-55 (408') of csg set 404'. 1-Guide shoe at 404'. Cmt'd w/250 sx of Class C 4% CaCl. Slurry wt. 14.8, 1.32 psi cu. ft./sx. Compressive Strength at 70 deg 1023 psi in 12 hours. PD 5:00 AM 12-4-78. Cmt did not circ. Filled hole to surface w/5 yds of Ready-mix. WOC 12 hrs, cut off, reduced hole to 12¼", drilled plug and tstd to 600#. OK & resumed drilling. TD 925' - Ran 27 jts of 8-5/8" 24# K-55 (927') of csg set at 925'. 1-guide shoe at 925' & insert float at 885'. Centr'z & baskets at 524' & 645'. Cmt'd as follows: 100 sx of Thick-set 6#/sx gilsonite, 1/4#/sx flocele 2% CaCl followed w/600 sx of Howco-Lite, 6#/sx gilsonite, 1/4#/sx flocele 2% CaCl & 200 sx of Class C 2% CaCl. Cmt did not circ. PD 7:30 AM 12-6-78. WOC 6 hrs, ran Temp. survey found top of cmt at 540'. Ran 1" sptd 50 sx of Class C 4% CaCl. PD 4:30 PM 12-6-78. WOC 3 hrs. Ran 1" tagged cmt at 540', sptd 50 sx Class C 4% CaCl. PD 7:30 PM 12-6-78. WOC 3 hrs, ran 1" tagged cmt at 525', sptd 50 sx Class C 4% CaCl. PD 11:00 PM 12-6-78. WOC 4 hrs, ran 1" cmt at 525', sptd 50 sx Class C 4% CaCl. PD 3:00 AM 12-7-78. WOC 2 hrs ran 1" top cmt at 428' sptd 100 sx Class C 4% CaCl. WOC ran 1" found cmt at 250'. Filled hole w/3 yds R.M. WOC 18 hrs, NU tstd BOP's to 2000#. OK, reduced hole to 7-7/8", drld plug Tstd to 600#. OK. Resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Tomlinson TITLE Geol. Secty DATE 12-12-78

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT H DATE DEC 14 1978

CONDITIONS OF APPROVAL, IF ANY: