

80-015-22746

Oseid- 25575

Prospect- 12401

Pool- 15472

Geol. Tops per B.A.

Abe 3943

Wolfcamp 5270

Canyon 7500

Strawn 8118

Atoka 8520

San Andres 458

Merrow LS 8700

Gleneta 1832

Merrow CI 8803

Tubb 3330

Chester 9020

1-31-79

Dual Laterolog

928-9090'

Comp. Neutron Formation  
Density  
0-9090'

NC TOPS PER LB

ABO - 3943  
WL - 5270  
PENN - 7094  
L.CAN - 7500  
STRAWN - 8118  
ATKA - 8520  
MDR.LS - 8700  
MDR.CI - 8803  
CHES - 9020

DISTRICT I

P.O. Box 1980, Hobbs NM 88240

DISTRICT II

P.O. Drawer DD, Artesia NM 88210


DISTRICT III

1000 Rio Brazos Rd., Aztec NM 87410

State of New Mexico  
Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088



CLSF

WELL API NO.	30-015-22746
Indicate Type of Lease	
State <input checked="" type="checkbox"/> FEE <input type="checkbox"/>	
State Oil & Gas Lease No.	L-6287
7. Lease Name or Unit Agreement Name	IRISH HILLS JE STATE COM
8. Well No.	1
9. Pool Name or Wildcat	DAGGER DRAW UPPER PENN, NORTH

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG AND ABANDON A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL ☐ GAS ☐  
WELL ☒ WELL ☐ OTHER ☐

2. Name of Operator  
**Yates Petroleum Corporation**

3. Address of Operator  
**105 South 4th., Artesia, NM 88210**

4. Well Location  
Unit Letter **G** : **1980** Feet From The **NORTH** Line and **1980** Feet From The **EAST** Line  
Section **12** Township **19S** Range **24E** NMPM **EDDY** COUNTY

10. Elevation (Show whether DF, RKB, RT, GR, etc.)  
**3604' GR**

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK: ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Yates Petroleum Corporation requests permission to plug & abandon as follows: **Notify OCD 24 hrs. prior to any work done**

MIRU - TOH w/ tubing. Attempt to recover 6800' of 4-1/2" casing. TIH w/ tubing & retrieving tool, latch onto RBP @ 8489' load hole w/ water before releasing RBP; POH.

RU wireline to set 4-1/2" CIBP @ 8454'. TIH w/ tubing to tag CIBP. Dump 35' Class C cement on top of CIBP. Set 4-1/2" CIBP @ 7693'; TIH w/ tubing to tag CIBP; dump 35' Class C cement on top of CIBP. Load hole w/ plugging mud & POH.

MIRU wireline to cut 4-1/2" casing @ 6800'. If casing cannot be pulled after it is cut, run a free point log to determine where it should be cut & pulled. Spot a 45 sk Class C w/ 2% CaCl2 plug across the casing stub. Pull the tubing up hole & circ clean. WOC 3 hrs & tag plug - re-set if necessary. **5700-5200**

Move tubing to spot 45 sk Class C w/ 2% CaCl2 plug from ~~4750-4650~~ **3800-3900** while keeping hole loaded w/ plugging mud. Pull tubing up hole & circ clean.

Move tubing to spot 45 sk Class C w/ 2% CaCl2 plug from ~~2750-2650~~ **3800-3900**, keep hole loaded w/ mud. Pull up, circ clean. **4750-4650**

Spot 35 sk Class C w/ 2% CaCl2 plug from 875-975' across intermediate casing shoe. Pull tubing up hole & circ clean; POH. WOC 3 hrs & tag plug - reset if necessary.

Spot 35 sk Class C w/ 2% CaCl2 plug from 354-454' across surface casing shoe. Pull tubing up hole & circ clean.

(continued on next page)

SIGNATURE Donna Click TITLE Operations Technician DATE 3/11/02

TYPE OR PRINT NAME DONNA CLICK TELEPHONE NO. 505-748-1471

(This space for State Use)

APPROVED BY [Signature] TITLE Field Rep DATE MAR 15 2002


CONDITIONS OF APPROVAL, IF ANY:

\* 45 sk plug 1700'-1800'

YATES PETROLEUM CORPORATION  
IRISH HILLS YESO JE STATE #1  
SECTION 12-19S-24E  
EDDY COUNTY, NEW MEXICO



POH; WOC 3 hrs & tag plug. Reset if necessary.  
Spot 15 sack Class C cement plug at surface.  
Remove all surface equipment & weld dry hole marker per regulations

  
DONNA CLACK  
OPERATIONS TECHNICIAN  
MARCH 11, 2002