

NEW MEXICO OIL CONSERVATION COMMISSION

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

RECEIVED

MAR 9 - 1979

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K-4587
7. Unit Agreement Name -
8. Farm or Lease Name State "14" Com
9. Well No. 1
10. Field and Pool, or Wildcat Undesignated (Morrow)
12. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER -
2. Name of Operator Southland Royalty Company ✓
3. Address of Operator 1100 Wall Towers West, Midland, Texas 79701
4. Location of Well UNIT LETTER <u>E</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>14</u> TOWNSHIP <u>19S</u> RANGE <u>29E</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3319.2' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drill 11" hole to 2856'. MW 10.0# vis 36. Ran BHG Sonic/GR-Caliper
Dual Laterolog w/RXO.
Ran 8 5/8" casing set @ 2856'. Cement with 900 sx Lite cement with 10# Gibsonite/sx
+ 2% Calcium Chloride, plus 300 sx Class "C" with 2% Calcium Chloride. PD @ 8:45 PM
12-16-78. Circulated 30 sx to surface. WOC 18 hrs. Nipple up 12" 3000# x 10" 5000#
csg. head and BOP. Test BOP and csg @ 1000# for 30 min. hold OK.
Drill ahead 7 7/8" hole. 8 5/8" casing in hole as follows:

Top Hole: 2243' 8 5/8" 24# K-55 ST&C (new)
Btm Hole: 613" ± S-80 ST&C (new)
Btm Csg: 2856'

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>C. Hamay</u>	TITLE <u>District Engineer</u>	DATE <u>3-7-79</u>
APPROVED BY <u>W. P. Gresser</u>	TITLE <u>SUPERVISOR, DISTRICT II</u>	DATE <u>MAR 12 1979</u>
CONDITIONS OF APPROVAL, IF ANY:		