

NEW MEXICO OIL CONSERVATION COMMISSION

DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Gulf Oil Corp.</i>		Lease <i>Eddy Gm State Con.</i>		Well # <i>2</i>	
Location of Well	Unit G <i>1980N 2180E</i>	Section <i>36</i>	Township <i>19</i>	Range <i>27</i>	County <i>Eddy</i>
Drilling Contractor			Type of Equipment <i>Rotary to start approx 1-15-79</i>		

* *Witness*

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>17 1/2 "</i>	<i>13 3/8 "</i>	<i>48</i>		<i>450</i>	<i>400 circ.</i>
<i>12 1/4 "</i>	<i>8 5/8 "</i>	<i>24</i>		<i>2800</i>	<i>1200 circ.</i>
<i>7 7/8 "</i>	<i>5 1/2 "</i>	<i>15.5-17</i>		<i>11200</i>	<i>500</i>

Casing Data:

Surface _____ joints of *8 5/8* inch *24* # Grade *J-SS*

(Approved) (Rejected)

Inspected by *M.S.* date *1/25/79*

Cementing Program

Size of hole *12 1/4* Size of Casing *8 5/8* Sacks cement required *1700'*Type of Shoe used *guide* Float collar used *inert* Btm 3 jts welded *yes*TD of hole *3000'* Set *3000'* Feet of *8 5/8* Inch *24* # Grade *J-SS*New-used csg. @ *3000'* with *200 2%* sacks neat cement around shoe+ *1500* sax *Hall. Lite* additives *6# gelsonite 1/4 floreal-2% occ*Plug down @ *4:00* (AM) (PM) Date *1/28/79*Cement circulated *yes* No. of Sacks *100*Cemented by *Halliburton* Witnessed by *Mike Stubbfield*

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____

*1 centralizer @ 2985'**last drill hole @ 1181'*