## NEW MEXICO OIL CONSERVATION COMMUSSION DRAWER DD ARTESIA, NEW MEXICO

Well # / Operator Hondo Guilling Lease Hondo - Barbara Location UnitJ Section Township Range County of Well 26 Edding Drilling Type of Equipment Contractor Hendo Dulling 6 Rotary 5 start gener, 2-15-79 \* Wilness APPROVED CASING PROGRAM Size of Hole | Size of Casing | Weight Per | New or Used Depth | Sacks Cement Foot 1378' 171/2" 350 48 an. 11 \*\* 1600 cise. \*871 24 7 1/8" 4 1/2" 71/8" 41/2" 11.60 9500 550 Casing Data: 133/8 @ 346-9Jts 68#-5-55 - W/350 54 - Classe - Circ The 37 joints of 8% inch 24 # Grade J-55 (Approved) (Rejected) date 7/24/79 Inspected by  $m\omega$ Cementing Program Size of hole\_1\\_\_\_\_Size of Casing 258 Sacks cement required 600 Type of Shoe used Gude Float collar used Josef Btm 3 jts welded Yes TD of hole 1600 Set 1636 Feet of 8% Inch 24 # Grade J-55 New-used csg. @ 1600 with 175 sacks neat cement around shoe  $\omega/2\%$  CC + 425 sax Helliburton Lite additives 5th Sinde persk + 14 \* Flocele Per Sk Plug down @ 7:00 (AM) (PM) Date 7/24/79 Cement circulated Yes No. of Sacks 45 Cemented by Halliburton Witnessed by MW Temp. Survey ran @ (AM) (PM) Date top cement @ Casing test @\_\_\_\_\_(AN) (PM) Date\_\_\_\_\_ Nethod Used Witnessed by Checked for shut off @ (AM) (PM) · Date Nethod used Nethod used Nemarks: Estimates - 1st It - tever other one 3rd - Sty - 7th - 9th Lest drlg preck 950-75

FIELD REPORT FOR CEMENTING OF WELLS