

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

RECEIVED

FEB 29 '88

Form C-103  
Revised 10-1-78

O. C. L.

ARTESIA, NEW MEXICO

Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name	
Hondo Barbara	
9. Well No.	
1	
10. Field and Pool, or Wildcat	
Four Mile Draw Morrow	
12. County	
Eddy	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Ralph Nix Oil, Inc. ✓
3. Address of Operator P. O. Box 440, Artesia, New Mexico 88210
4. Location of Well UNIT LETTER J, 1980 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 11 TOWNSHIP 19S RANGE 26E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3303' GL

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☒  
CHANGE PLANS ☐  
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOBS ☐  
OTHER ☐  
ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- Set CIBP @ 9400' and set 100' cmt cap.
- Load hole with mud.
- Determine free point and cut casing at a required cement plug interval as outlined below and spot cement 50' in and out of casing.
- Spot 25 sx @ 7550'-7450' (Penn top 7500').
- Spot 25 sx @ 7025'-6925' (Wolfcamp 6972').
- Spot 25 sx @ 6700'-6600' (3rd Bone Springs Sand).
- Spot 25 sx @ 3950'-3850' (Top Bone Springs).
- Spot 25 sx @ 3160'-3060' (Glorieta).
- Spot 35 sx @ 1650'-1550' and tag (Water protection string).
- Spot 35 sx @ 300'-400' (Surface pipe).
- Surface plug and regulation dry hole marker.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ralph Nix

TITLE President

DATE 2-26-88

APPROVED BY Thane Williams

TITLE

OIL AND GAS DIVISION

DATE

CONDITIONS OF APPROVAL, IF ANY: