

NO. OF COPIES RECEIVED	
DISTRIBUTION	
ANTA FE	1
H.E.	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

DEC 3 - 1979

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDARY NOTICES AND REPORTS ON WELLS **O. C. C.**
ARTESIAN OFFICE

(DO NOT USE THIS FORM FOR APPLICATIONS TO OBTAIN OR TO RENEW OR REVOKE A WELL CASH OR OTHER INTERESTS)

☐ OIL WELL ☒ GAS WELL ☐ OTHER

Name of Operator
Southland Royalty Company

Address of Operator
1100 Wall Towers West, Midland, Texas 79701

Location of Well
UNIT LETTER **B** **660** FEET FROM THE **north** LINE AND **1980'** FEET FROM
THE **east** LINE, SECTION **32** TOWNSHIP **19S** RANGE **28E** NADPAC.

13. Elevation (Show whether DF, RT, GR, etc.)
3366.9' GR.

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
648

7. Unit Agreement Name

8. Farm or Lease Name
State "32" Com.

9. Well No.
1

10. Field and Pool, or Wildcat
Winchester (Morrow)

12. County
Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ REMEDIAL WORK ☐ ALTERING CASING ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

WELL OR ALTER CASING ☐ OTHER ☐ CASING TEST AND CEMENT JOB ☒

OTHER ☐

SUBSEQUENT REPORT OF:

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drill 7 7/8" hole to 11,136'. MW 10.0, vis 38 wl 4. Ran Dresser Atlas CNL-FDC w/GR-Caliper and Dual Laterolog w/RXO. Ran 4 1/2" csg. set @ 11,135'. Cement 1st stage w/200 sx. Lite w/5# KCL/sx. 3/4% CFR-2. Plug down @ 6:20 A.M. 11-13-79. Cement 2nd stage via "DV" tool @ 7120' w/260 sx. Class "H" cement w/1/2% CFR-2 and 5# KCL/sx. Plug down @ 10:50 A.M. 10-13-79. T/cement by temperature survey @ 5210'. WOC 5 days. Rig up completion unit, drill out "DV" tool, pressure test csg. to 2000# for 30 min., hold OK. Initiate completion. 4 1/2" casing in hole as follows:

Top Hole: 470' 4 1/2" 11.6# N-80 Buttress
2513' 4 1/2" 11.6# N-80 LT&C
4094' 4 1/2" 11.6# K-55 ST&C
3499' 4 1/2" 11.6# N-80 LT&C
Btm Hole: 559' 4 1/2" 13.5# N-80 LT&C
Set @ 11,135'

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

APPROVED BY C. Hawen Can TITLE District Engineer DATE 11-28-79

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE DEC 4 - 1979

CONDITIONS OF APPROVAL, IF ANY: