

RECEIVED

DEC 17 1979

O. C. C.
ARTEGIA, OFFICE

DST Information
State "32" Com. #1

Attachment C-105

DST #1

30" preflow, Med to good blow, G.T.S. 32". 18 LB Max SFP,
Calc 46 MCFD - 60" ISIP.
60" T.O. w/G.T.S. 22lb Max SFP, Calc 52 MCFD.
120" FSIP
Rec. 320' Free oil, 180' Water.
Sampler: 140 lb. press., 105 cu. ft. gas, 640 cc oil, 42 G,
86°F. 340 cc Water, CL: 15000 PPM
IHP 9067, 1st IFP 99.1, 30" FFP 161.7, 60" ISIP 2303.1, 2nd IFP 111.6,
60" FFP 211.8, 120" FSIP 2303.1, FHP 3054.4, BHT 123°F.
CL: Pit 14000 PPM, Rec 15000 PPM.

DST #2

30" preflow, Immed. good blow, GTS 18". 7 lb Max SFP, 1/4" chock.
60" ISIP, 60" TO w/GTS. 9 lb. max SFP, 1/8" choke, 120" FSIP.
Rec: 30' Free oil, 43 G @ 76°F. 240' Drlg. fluid, 103,000 PPM chl.
Sampler: 90 lb press, .75 cu ft. gas, trace water, 105,000 PPM chl.
IHP 4267, 1st IFP 87, 30" FFP 137, 60" ISIP 763, 2nd IFP 74, 60"
FFP 149, 120" FSIP 437, FHP 4194, BHT 136°F.
Chl: Pit 106,000 PPM, Rec 103,000 PPM.

DST #3

30" preflow, strong blow, GTS 3". 260 lb max SFP, Calc 2500 MCFD,
13/32" choke. 60" ISIP, 60" TO w/GTS 350 lb. Max SFP, Calc 3300 MCFD,
19/32" choke. 120" FSIP.
Rec: Reversed sample distillate
Sampler: 200 lb. press, 4.0 cu ft. gas, 40 cc distillate, 62 G @ 78°F.
IHP 4690, 1st IFP 382, 30" FFP 762, 60" ISIP 3575, 2nd IFP 572, 60" FFP
952, 120" FSIP 3347, FHP 4690, BHT 155°F, Cl Drlg fluid: 90000 PPM.

DST #4

30" preflow, weak blow. 60" ISIP, 60" TO w/weak blow. 180" FSIP.
Rec: 120' Drlg. mud
Sampler: 100 lb. press, 1200 cc drlg mud
Bottom Tool
IHP 5281, 1st IFP 108, 30" FFP 152, 60" ISIP 477, 2nd IFP 108,
60" FFP 152, 180" FSIP 868, FHP 5259, BHT 164°F.

C. C. C.
Harvey Carr