

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Collins + Collins</i>		Lease <i>7000</i>		Well # <i>1</i>	
Location of Well	Unit <i>E</i> <i>2310N 896W</i>	Section <i>32</i>	Township <i>19</i>	Range <i>27</i>	County <i>Eddy</i>
Drilling Contractor <i>Yucca Drilling Co.</i>			Type of Equipment <i>Rotary 7.5" 3-12-79</i>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>7 7/8"</i>	<i>4 1/2"</i>	<i>11 #</i>		<i>375</i>	<i>120 cins.</i>

Casing Data:
Surface _____ joints of _____ inch _____ # Grade _____
(Approved) (Rejected) _____

Inspected by _____ date _____

Cementing Program

Size of hole *7 7/8* Size of Casing *4 1/2"* Sacks cement required *150*
Type of Shoe used *guide* Float collar used *No* Btm 3 jts welded *yes*
TD of hole *385'* Set *383'* Feet of *4 1/2* Inch *11* # Grade _____
New-used csg. @ *383'* with *150* sacks neat cement around shoe
+ _____ sax _____ additives _____

Plug down @ *10:15* (AM) (PM) Date *3/22/79*

Cement circulated *No* No. of Sacks *0*

Cemented by *Denton* Witnessed by *Mike Stillfield*

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: *Operator will ready-mix hole to surface.*

centralizers @ 380'-350'-320' *No wth. in hole*