

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

RECEIVED

APR 12 1979

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- ARTESIA, OFFICE		5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
2. Name of Operator Southland Royalty Company ✓		5. State Oil & Gas Lease No. L-6702
3. Address of Operator 1100 Wall Towers West, Midland, Texas 79701		7. Unit Agreement Name -
4. Location of Well UNIT LETTER J 1980 FEET FROM THE south LINE AND 2150 FEET FROM THE east LINE, SECTION 30 TOWNSHIP 19S RANGE 28E NMPM.		8. Farm or Lease Name State "30" Com.
15. Elevation (Show whether DF, RT, GR, etc.) 3465.0' GR		9. Well No. 1
		10. Field and Pool, or Wildcat Angel Ranch (Morrow)
		12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud well @ 1:00 P.M. 4-8-79 by Hondo Drilg. Co. Rig #5. Drill 15" hole to 365'.
Ran 11 3/4" 42# H-40 ST&C csg. set @ 365'. Cement with 300 sx Class "C" cement with 2% Calcium Chloride. Plug down @ 12:30 A.M. 4-9-79. Cement circulated.
WOC 18 hrs. Nipple up BOP. Test csg. and BOP @ 1000' for 30 min., hold O.K.
Drill ahead 11" hole.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED C. Harvey Carr TITLE District Engineer DATE 4-10-79

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE APR 13 1979

CONDITIONS OF APPROVAL, IF ANY: