

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

MAY 31 1979

O. C. C.
ARTEBIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input type="checkbox"/>
2. Name of Operator Southland Royalty Company ✓		5. State Oil & Gas Lease No. L-6702
3. Address of Operator 1100 Wall Towers West, Midland, Texas 79701		7. Unit Agreement Name
4. Location of Well UNIT LETTER <u>J</u> <u>1980</u> FEET FROM THE <u>south</u> LINE AND <u>2150</u> FEET FROM <u>east</u> THE <u>30</u> LINE, SECTION <u>19S</u> TOWNSHIP <u>28E</u> RANGE <u>NMPM.</u>		8. Farm or Lease Name State 30 Com.
15. Elevation (Show whether DF, RT, GR, etc.) 3465.0' GR		9. Well No. 1
		10. Field and Pool, or Wildcat Angell Ranch (Morrow)
		12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drill 7 7/8" hole to TD of 11,400'. MW 9.9 vis 39 wl 4.5
Ran Compensated Neutron-Formation Density w/GR-Caliper and
Dual Laterolog w/RXO
Ran 4 1/2" casing set @ 11,203'. Cement w/300 sx Lite w/.3% CFR-2 and
5# KCL/sx plus 650 sx Class "H" w/.75% CFR-2 and 5# KCL/sx.
Plug down @ 3:00 A.M. 5-20-79
Temperature survey T/cmt @ 7500'. Will test csg w/completion rig.
4 1/2" csg in hole as follows:

Top Hole:	577'	4 1/2"	11.6#	N-80	Buttress
	2517'	4 1/2"	11.6#	N-80	LT&C
	4171'	4 1/2"	11.6#	K-55	ST&C
	3433'	4 1/2"	11.6#	N-80	LT&C
Btm Hole:	505'	4 1/2"	11.6#	S-95	LT&C
	11,203'				

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED C. Hamer Can TITLE District Engineer DATE 5-29-79

APPROVED BY W. A. Grasset TITLE SUPERVISOR, DISTRICT II DATE JUN 4 1979

CONDITIONS OF APPROVAL, IF ANY: