

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other Instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-064670

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

State-Federal "22" Comm.

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated (Morrow)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 22, T-19-S, R-28-E

12. COUNTY OR PARISH

Eddy

13. STATE
New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

RECEIVED

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Southland Royalty Company

JUN 20 1979

3. ADDRESS OF OPERATOR

1100 Wall Towers West, Midland, Texas 79701 O.C.C.
ARTESIA, OFFICE4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

1980' FNL & 990' FWL, Sec. 22, T-19-S, R-28-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3411.2 GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Set 8 5/8" casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drill 11" hole to 2510' MW 9.5, Vis 35.

Ran 8 5/8" 24# K-55 ST&C csg set @ 2508'.

Cemented w/1300 sx Halli-Lite w/5# Gilsonite, 1/4# Flocele & 5# salt/sk,
plus 150 sx Class "C" w/2% C.C. Cement Circulated back to surface,
displace 95 sx to pit.

Plug down @ 12:20 p.m., 6-7-79. WOC 18 hrs.

Install double ser 900 BOP, ser 900 Hydril and drilling head.

Test BOP and casing to 1500 PSI for 30 min. held ok.

Drill ahead 7 7/8" hole

RECEIVED

JUN 18 1979

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

C. Harney

TITLE

District Engineer

DATE

6-15-79

(This space for Federal or State office use)

APPROVED BY

ALBERT R. STALL

TITLE

ACTING DISTRICT ENGINEER

DATE

JUN 19 1979

CONDITIONS OF APPROVAL, IF ANY: