

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	✓

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

JUN 13 1979

O. C. C.
ARTESIA, OFFICE

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>	
5. State Oil & Gas Lease No. E-2943	
7. Unit Agreement Name	
8. Farm or Lease Name State 16A Com.	
9. Well No. 1	
10. Field and Pool, or Wildcat Turkey Track (Morrow)	
12. County Eddy	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Southland Royalty Company ✓
3. Address of Operator 1100 Wall Towers West, Midland, Texas 79701
4. Location of Well UNIT LETTER O 990 FEET FROM THE south LINE AND 1980 FEET FROM THE east LINE, SECTION 16 TOWNSHIP 19S RANGE 29E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3339.1' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drill 11" hole to 2800' MW 10.1# vis 37
Ran BHC Acoustic - GR Caliper & Dual Laterolog w/RXO
Ran 8 5/8" csg. set @ 2800'. Cement w/950 sx Lite cement + 250 sx. Class "C" cement w/2% c.c. Cement circulated.
Plug down @ 8:00 A.M. 5-28-79 W.O.C. 18 hrs.
Install double 10" Ser 900 BOP & 10" Ser. 900 Hydril & Drilling Head. Test casing & BOP to 1500 psi for 30 min. hold OK. Drill ahead 7 7/8" hole.
8 5/8" casing in hole as follows:
Top Hole: 2287' 8 5/8" 24# K-55 ST&C
Bottom Hole" 513' 8 5/8" 24# S-80 ST&C
Set @ 2800'

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED C. Hanney Can TITLE District Engineer DATE 6-12-79
APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE JUN 15 1979
CONDITIONS OF APPROVAL, IF ANY: