

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPlicate\*  
(Other Instructions on reverse side)Form approved.  
Budget Bureau No. 42-R1424.  
5. LEASE DESIGNATION AND SERIAL NO.

NM-14118

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Allison "CQ" Federal

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT Und.

Boyd Morrow

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREASec. 12-19S-24E  
Unit L NMPM

12. COUNTY OR PARISH

Eddy

13. STATE

NM

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

JUL 23 1979

O.C.C.

ARTESIA OFFICE

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, NM

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

1980' FSL &amp; 660' FWL of Sec. 12-19S-24E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3602' GR

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

TD 9260'; PBTD 9236' - Ran 228 joints of 4½" casing as follows: 22 joints 11.6# N-80 (721'), 150 joints 10.5# ST&C K-55 (6235'), 56 joints 11.6# K-55 LT&C (2300') (Total 9256') of casing set at 9256'. 1-Guide shoe at 9256', Diff-Fill Collar at 9236' and 8-centralizers. Cemented w/250 gallons of mud flush, 430 sacks Howco-Lite, 3/10% Halad-22, 5/10% CFR-2, 5#/sack KCL and 150 sacks Class H 3/10% Halad-22, 5/10% CFR-2, 5#/sack KCL. PD 10:00 PM 7-9-79. WOC and tested to 1500#. OK. Ran Temperature Survey and found top of cement at 5800'.

RECEIVED

JUL 19 1979

U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

*Albert R. Stale*

TITLE

Geol. Secty.

DATE 7-18-79

(This space for Federal or State office use)

Orig. Sgd.) ALBERT R. STALE

TITLE

ACTING DISTRICT ENGINEER

DATE JUL 20 1979

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY: