

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Amoco Prod. Co.</i>		Lease <i>State H.E. Com.</i>		Well # <i>1</i>	
Location of Well	Unit <i>19805+4</i>	Section <i>11</i>	Township <i>19</i>	Range <i>27</i>	County <i>Eddy</i>
Drilling Contractor <i>M.G.F. Dry. Rig-23</i>			Type of Equipment <i>Rotary to start 7-3-79</i>		

* *witness* APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>17 1/2"</i>	<i>13 3/8"</i>	<i>48</i>		<i>500</i>	<i>cin.</i>
<i>12 1/4"</i>	<i>9 5/8"</i>	<i>36</i>		<i>2500</i>	<i>cin.</i>
<i>8 3/4"</i>	<i>5 1/2"</i>	<i>15.5+17</i>		<i>10600</i>	

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____
(Approved) (Rejected) _____

Inspected by _____ date _____

Cementing Program

Size of hole *12 1/4* Size of Casing *9 5/8* Sacks cement required _____

Type of Shoe used *guide* Float collar used *yes* Btm 3 jts welded *yes*

TD of hole *3300'* Set *3300'* Feet of *9 5/8* Inch *36* # Grade *K-55*

New-used csg. @ *3300'* with *200* yds. sacks neat cement around shoe

+ *2180* sax *Hall-Lite* additives *5# gilsonite - 1/4# floe - 8# salt*

Plug down @ *1:20* (AM) (PM) Date *7/30/79*

Cement circulated *yes* No. of Sacks *300*

Cemented by *Hall-Lite* Witnessed by *Mike Stubblefield*

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____

centralizers @ 3260' - 3300' *last dry hole @ 3146'*
(Bone section)