

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	/
FILE	/ ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

OCT 25 1979

O. C. C.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
2. Name of Operator TENNECO OIL COMPANY ✓	5. State Oil & Gas Lease No. B-9739
3. Address of Operator 6800 Park Ten Blvd., Suite 200 N., San Antonio, TX. 78213	7. Unit Agreement Name N/A
4. Location of Well UNIT LETTER N 660 FEET FROM THE SOUTH LINE AND 1980 FEET FROM THE WEST LINE, SECTION 11 TOWNSHIP 19S RANGE 29E NMPM.	8. Farm or Lease Name STATE HL 11
	9. Well No. 1
	10. Field and Pool, or Wildcat Undesignated Turkey Tract (Morrow)
15. Elevation (Show whether DF, RT, GR, etc.) 3377' GR	12. County EDDY

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8/11/79 - Set 13 3/8" New 54.5# (6Jts) K 55 ST&C @ 235' - Cemented

Bottom W/400 SxS "C" + 2% CACL₂ + 1/4# Sx Celloflake

Displaced within 30' of shoe. Cut window in 20"

Conductor (40' Conductor Pipe Set) and topped out with 27 cubic yds.

of Redimix Cement. Hole filled and stayed full. WOC 18Hrs - Tested 600 PSI.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED F. R. Bell TITLE Staff Production Analyst DATE 10-23-79

APPROVED BY W. A. Gussitt TITLE SUPERVISOR, DISTRICT II DATE NOV 1 1979

CONDITIONS OF APPROVAL, IF ANY: