

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 2 years after the completion of any newly-drilled or deepened well. It shall be accompanied by or copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 35 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1155.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy 60	T. Canyon 10080	T. Ojo Alamo	T. Penn. "B"
T. Salt 310	T. Strawn 10350	T. Kirtland-Fruitland	T. Penn. "C"
T. Salt 1125	T. Atoka 10610	T. Pictured Cliffs	T. Penn. "D"
T. Yates 1310	T. Miss 11590	T. Cliff House	T. Leadville
T. 7 Rivers 1680	T. Devonian	T. Menefee	T. Madison
T. Queen 2110	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg 2640	T. Montoya	T. Mancos	T. McCracken
T. San Andres	T. Simpson	T. Gallup	T. Ignacio Qtzite
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinberry	T. Gr. Wash	T. Morrison	T.
T. Tubb	T. Granite	T. Todilto	T.
T. Drinkard	T. Delaware Sand 3440	T. Entrada	T.
T. Abc	T. Bone Springs 4740	T. Wingate	T.
T. Wolfcamp 9150	T. Morrow 11250	T. Chinle	T.
T. Penn. 9550	T.	T. Permian	T.
T. Cisco (Bough C) 9650	T.	T. Penn. "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from 11252- to 11260	No. 4, from 11386 to 11418
No. 2, from 11305 to 11310	No. 5, from 11440 to 11452
No. 3, from 11346 to 11366	No. 6, from 11502 to 11532

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
No. 2, from.....to.....feet.....
No. 3, from.....to.....feet.....
No. 4, from.....to.....feet.....

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	310	310	Anhy	10210	10350	140	LS
310	1125	815	Salt	10350	10610	260	SH
1125	1680	555	Anhy & SD	10610	10870	260	SH & SD
1680	2110	430	Dol & SD	10870	11250	380	LS & SH
2110	2640	530	DOL & SD	11250	11590	340	SD; SH, LS.
2640	3440	800	DOL.	11590	11636	46	SH
3440	4740	1300	SD				
4740	7020	2280	LS				
7020	7440	420	SD				
7440	7740	300	LS				
7740	8120	380	SD				
8120	8510	390	LS				
8510	8720	210	SD				
8720	9150	430	LS & SH				
9150	9500	350	LS & SH				
9500	10080	580	LS & SH				