

Form 9-331  
(May 1963)UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN 1 PLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.  
5. LEASE DESIGNATION AND SERIAL NO.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		2. NAME OF OPERATOR Joe Don Cook		3. ADDRESS OF OPERATOR PC Box 159, Roswell, NM 88201		4. LOCATION OF WELL (Report location clearly and in accordance with State requirements. See also space 17 below.) At surface 1980' FNL & 660' FWL		5. LEASE DESIGNATION AND SERIAL NO. NM 3620		6. IF INDIAN, REPORT INDIAN NAME		7. UNIT AGREEMENT NAME MAR 12 1980		8. FARM OR LEASE NAME ARTESIA, OFFICE Hannifin-Federal		9. WELL NO. 2		10. FIELD AND POOL, OR WILDCAT Undesignated Morrow		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 1-19S-31E		12. COUNTY OR PARISH Eddy		13. STATE NM	
14. PERMIT NO. --				15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3624 GR				16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data																	

RECEIVED

MAR 10 1980

U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

Completion casing

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

3-4-80 Ran 4½" N-80

KB connection	18.00'
40 jts. (13.5 lbs.)	2067.68'
194 jts. (11.6 lbs.)	8225.30'
45 jts. (13.5 lbs.)	1901.54'
Float collar	1.58'
Shoe jt., (13.5 lbs.)	41.85'
Shoe	.83'
	12256.78'
Less cutoff	- 6.78
Landed @ TD	12250'

Cemented with 300 sx. Class "H" with 3% KCl, 1% D-19, 0.22% R-5, 0.2% A-2.  
Plug down @ 8:30 pm 3-3-80. Ran Temp. survey, cement top 11250.

18. I hereby certify that the foregoing is true and correct

SIGNED

Charles W. Sanders

TITLE Vice President

DATE 3-6-80

(This space for Federal or State office use)

(Orig. S&amp;L) GEORGE H. STEWART

TITLE ACTING DISTRICT ENGINEER

DATE MAR 11 1980

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY: