

CISF

N.M.O.C.D. COPY

Form 9-331
Dec. 1973

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐ **SEP 28 1979**
2. NAME OF OPERATOR **Amoco Production Company** **D.O.C. ARTESIA OFFICE**
3. ADDRESS OF OPERATOR
P.O. Box 68 Hobbs, NM 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FSL X 2310' FWL, Sec. 35 (Unit N, SE 1/4, SW 1/4)
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

- | | | |
|----------------------|--------------------------|-------------------------------------|
| TEST WATER SHUT-OFF | <input type="checkbox"/> | <input checked="" type="checkbox"/> |
| FRACTURE TREAT | <input type="checkbox"/> | <input type="checkbox"/> |
| SHOOT OR ACIDIZE | <input type="checkbox"/> | <input type="checkbox"/> |
| REPAIR WELL | <input type="checkbox"/> | <input type="checkbox"/> |
| PULL OR ALTER CASING | <input type="checkbox"/> | <input type="checkbox"/> |
| MULTIPLE COMPLETE | <input type="checkbox"/> | <input type="checkbox"/> |
| CHANGE ZONES | <input type="checkbox"/> | <input type="checkbox"/> |
| ABANDON* | <input type="checkbox"/> | <input type="checkbox"/> |
| (other) | <input type="checkbox"/> | <input type="checkbox"/> |

5. LEASE ☒
LC-029392-a
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Greenwood Pre-Grayburg Unit E Com
9. WELL NO.
13
10. FIELD OR WILDCAT NAME
Und. Shugart Penn
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
35-18-31
12. COUNTY OR PARISH
Eddy
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3627.8 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled to a TD of 12,006' and ran 5 1/2" 17#, 20#, and 23# casing set at 12,006'. Cemented with 1500 sx Trinity Lite cement and 500 sx Class H cement. Plug down 8:00 AM 9-19-79. Cement did not circulate. Top of cement found by temperature survey at approximately 3,265'. Will test casing when move in completion unit.

RECEIVED

SEP 27 1979

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Ray Cox TITLE Admin. Supervisor DATE 9-21-79

APPROVED BY George H. Silvestri (This space for Federal or State office use)
ACTING DISTRICT ENGINEER DATE SEP 27 1979

CONDITIONS OF APPROVAL, IF ANY:

0-4-USGS-A 1-Hou 1-Susp 1-BD 1-Cities Service
1-Conoco