

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.O.S.	
LAND OFFICE	
OPERATOR	1

RECEIVED

AUG 15 1979

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
L-6520	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT DEPTH. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

O. C. C.

ARTESIA OFFICE

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator		Parkway West
The Petroleum Corporation		8. Farm or Lease Name
3. Address of Operator		Parkway West Unit
1440 Midland National Bank Tower, Midland, TX 79701		9. Well No.
4. Location of Well		6
UNIT LETTER O, 1980 FEET FROM THE East LINE AND 660 FEET FROM THE South LINE, SECTION 21 TOWNSHIP 19-S RANGE 29-E NMPM.		10. Field and Pool, or Wildcat
		Undesignated West Parkway (Morrow)
15. Elevation (Show whether DF, RT, GR, etc.)		12. County
3329.7 GR		Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well @ 1:00 pm, August 10, 1979, with Warton Drilling rig. Drilled 17½" hole to 365' depth. Ran 9 joints 13-3/8" H-40 ST & C 48# new casing and cemented at 365' with 200 sx Howco Thikset with 12#/sx gilsonite, ¼#/sx flocele, 2% CaCl₂ and 375 sx Class "C" cement containing 2% CaCl₂. Plug down at 3:00 am, August 11, 1979. Circulated 100 sx. WOC 21½ hours. Tested casing with 600 psi - 30 minutes - OK. Drilled out with 12¼" bit.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED J. K. G. [Signature] TITLE District Engineer DATE 8-13-79

APPROVED BY W. G. Gussert TITLE SUPERVISOR, DISTRICT II DATE AUG 16 1979

CONDITIONS OF APPROVAL, IF ANY: