

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Southland Royalty Co.</u>		Lease <u>State 25 Com.</u>		Well # <u>1</u>	
Location of Well	Unit <u>19805</u> <u>2/30W</u>	Section <u>25</u>	Township <u>19</u>	Range <u>29</u>	County <u>Eddy</u>
Drilling Contractor <u>Hondo Dry Co. Rig 5</u>		Type of Equipment <u>Rotary to Start approx 8-21-79</u>			
* <u>Witness</u> APPROVED CASING PROGRAM					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
15"	11 3/4"	42		360	425 circ.
* 11"	8 5/8"	24		3150+	1400 "
7 7/8"	4 1/2"	11.6		12000	1000
Casing Data:					
Surface _____ joints of _____ inch <u>24+28</u> # Grade <u>S-80 K-55</u>					
(Approved) (Rejected)					
Inspected by <u>M. S.</u> date <u>8/29/79</u>					
Cementing Program					
Size of hole <u>11"</u> Size of Casing <u>8 5/8</u> Sacks cement required _____					
Type of Shoe used <u>guide</u> Float collar used <u>insert</u> Btm 3 jts welded <u>yes</u>					
TD of hole <u>4000'</u> Set <u>4000'</u> Feet of <u>8 5/8</u> Inch <u>24</u> # Grade <u>S-80 K-55</u>					
New-used csg. @ <u>4000'</u> with <u>200</u> 29 sacks neat cement around shoe					
+ <u>500</u> sax <u>Hall. Lite</u> additives <u>10# grease, 1/4# floe, 8# salt</u>					
Plug down @ _____ (AM) (PM) Date _____					
Cement circulated _____ No. of Sacks _____					
Cemented by <u>Halliburton</u> Witnessed by <u>Mike Stubbelfeld + Mike Williams</u>					
Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks: _____					
DV Tool @ 1791'					
centerline @ 3960'					
2nd stage + 700sx Hall. Lite					
+ 100sx class C					
Plug down @ 11:10PM Circ 125 SX to the Pit					

last circ @ 1885 + regained

last dry break @ 3960'