

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Gates Petr. Corp.</i>		Lease <i>SRG state KZ</i>		Well # <i>2</i>	
Location of Well	Unit <i>660N 1980E</i>	Section <i>1</i>	Township <i>19</i>	Range <i>24</i>	County <i>Eddy</i>
Drilling Contractor <i>Landis Drilling Co.</i>		Type of Equipment <i>Rotary to start approx. 9-5-79</i>			
* witness APPROVED CASING PROGRAM					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>17 1/2</i>	<i>13 3/8"</i>	<i>48</i>		<i>400</i>	<i>300 cwt.</i>
<i>12 1/4</i>	<i>8 7/8"</i>	<i>24</i>		<i>900</i>	<i>500 "</i>
<i>7 7/8"</i>	<i>5 1/2" or 4 1/2"</i>	<i>15-5417 or 10.5</i>		<i>9200</i>	<i>300 SK</i>
Casing Data: <i>11-6</i>					
Surface _____ joints of _____ inch <i>24</i> # Grade <i>J-55</i>					
(Approved) (Rejected)					
Inspected by _____ date _____					
Cementing Program					
Size of hole <i>12 1/2</i> Size of Casing <i>8 5/8</i> Sacks cement required _____					
Type of Shoe used <i>guide</i> Float collar used <i>insert</i> Btm <i>2</i> jts welded <i>yes</i>					
TD of hole <i>923</i> Set <i>923</i> Feet of <i>8 5/8</i> Inch <i>24</i> # Grade <i>J-55</i>					
New-used csg. @ <i>923</i> with <i>150 270cc</i> sacks neat cement around shoe					
+ <i>400</i> sack <i>50-50 pox</i> additives <i>6# Kelite, 1/4# redoflake, 270cc</i>					
Plug down @ <i>1:30</i> (AM) (PM) Date <i>9/16/79</i>					
Cement circulated <i>yes</i> No. of Sacks <i>80</i>					
Cemented by <i>Dowell</i> Witnessed by <i>Mike Stubbfield</i>					
Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks: _____					
1 centralizer @ 884'					
last drill break @ 822'					