

NO. OF COPIES RECEIVED	
DISTRIBUTION	
ANTA FC	/
FILE	/
J.S.G.S.	
LAND OFFICE	
OPERATOR	/

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

SEP 26 1979

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

O. C. C.

ARTESIA, OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)

5a. Indicate Type of Lease

State ☒ Fee ☐

5. State Oil & Gas Lease No.

L-2919

7. Unit Agreement Name

8. Farm or Lease Name

SRC State "KZ"

9. Well No.

1 2

10. Field and Pool, or Wildcat

Und. Morrow

12. County

Eddy

OIL ☐ GAS ☒ OTHER-

Name of Operator

Yates Petroleum Corporation

Address of Operator

207 South 4th Street - Artesia, NM 88210

Location of Well

UNIT LETTER B 660 FEET FROM THE North LINE AND 1980 FEET FROM

THE East LINE, SECTION 1 TOWNSHIP 19S RANGE 24E NMPM.

15. Elevation (Show whether DF, RT, CR, etc.)

3675' GR

6. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

TEMPORARILY ABANDON ☐

PULL OR ALTER CASING ☐

OTHER ☐

PLUG AND ABANDON ☐

CHANGE PLANS ☐

REMEDIAL WORK ☐

COMMENCE DRILLING OPNS. ☒

CASING TEST AND CEMENT JOBS ☒

OTHER ☐

ALTERING CASING ☐

PLUG AND ABANDONMENT ☐

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1503.

Spudded a 17½" hole at 4:30 PM 9-14-79. TD 410'. - Ran 9 joints of 13-3/8" 48# J-55 (412') of casing set at 410'. 1-Guide shoe at 410'. Insert float at 370'. Cemented w/400 sacks of Class C 4% CaCl. Slurry wt. 14.8, 1.32 cu. ft./sx. Compressive Strength at 70 degrees, 1023 psi in 12 hours. Cement circulated 60 sacks to surface. PD 8:30 AM 9-15-79. WOC 12 hours, cut off, reduced hole to 12¼", drilled plug and tested to 600#. OK and resumed drilling. TD 924'. Ran 23 joints of 8-5/8" 24# J-55 ST&C (928') of casing set at 924'. 1-Guide shoe at 924' and float at 884'. Cemented w/400 sacks 50/50 poz, 6#/sx Kolite, 1/4#/ sack celloflake 2% CaCl, 150 sacks of Class C 2% CaCl. PD 1:45 PM 9-16-79. Cement circulated 60 sacks to surface. WOC 18 hours, NU and tested BOP's to 1500#, OK, reduced hole to 7-7/8", drilled plug and tested to 600# OK and resumed drilling.

16. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED

TITLE Geol. Secty.

DATE 9-25-79

APPROVED BY

TITLE SUPERVISOR, DISTRICT

DATE

SEP 27 1979

CONDITIONS OF APPROVAL, IF ANY