

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 30 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radioactivity logs run on the well and a summary of all special tests conducted, including drill stem tests. All data reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quantity dictated except on state land, where six copies are required. See Rule 1135.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico			Northwestern New Mexico		
T. Anhy		Lower Canyon 7462	T. Ojo Alamo		T. Penn. "B"
T. Salt		T. Strawn 8076	T. Kirtland-Fruitland		T. Penn. "C"
B. Salt		T. Atoka 8439	T. Pictured Cliffs		T. Penn. "D"
T. Yates		T. Miss 9036	T. Cliff House		T. Leadville
T. 7 Rivers		T. Devonian	T. Menefee		T. Madison
T. Queen		T. Silurian	T. Point Lookout		T. Elbert
T. Grayburg		T. Montoya	T. Mancos		T. McCracken
T. San Andres	594	T. Simpson	T. Gallup		T. Ignacio Quartz
T. Glorieta	1978	T. McKee	Base Greenhorn		T. Granite
T. Paddock		T. Ellenburger	T. Dakota		T. _____
T. Blinbry		T. Gr. Wash	T. Morrison		T. _____
T. Tubb		T. Granite	T. Todilto		T. _____
T. Drinkard		T. Delaware Sand	T. Entrada		T. _____
T. Abo	4026	T. Bone Springs	T. Wingate		T. _____
T. Wolfcamp	5260	T. Morrow 8688	T. Chinle		T. _____
T. Penn.		T. Chester 8908	T. Permian		T. _____
T. Cisco (Bough C)		T. _____	T. Penn. "A"		T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.
No. 2, from.....to.....feet.
No. 3, from.....to.....feet.
No. 4, from.....to.....feet.

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	306	306	Surface	DRILL STEM TEST			
306	408	102	Anhy, red bed	DST #1 - 8266-8340' - TO 30", SI 90", TO 60", SI 120" - TO w/fair blo, Reop. w/weak blo. Recovered: 60' DM. Sampler: 2000 cc DM, no gas, no press. Pressures: HP 3955-3955; IFP 18-198, ISIP 202; FFP, 18-18, FSIP 198.			
408	626	218	Red & rock				
626	869	243	Anhy, lime and sand				
869	924	55	Sand and Anhy				
924	4235	3311	Dolomite				
4235	4524	289	Lime, shale and dolo				
4524	9140	4616	Lime and shale				