

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
ANTA FE	1
ILE	1 ✓
J.S.G.S.	
LAND OFFICE	
OPERATOR	1

RECEIVE
NEW MEXICO OIL CONSERVATION COMMISSION
OCT 23 1979

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

O. C. C.
ARTESIA, OFFICE

5a. Indicate Type of Lease State ☒ Fee ☐
5. State Oil & Gas Lease No. OG-783
7. Unit Agreement Name
8. Farm or Lease Name Greasewood BD State
9. Well No. 1 2
10. Field and Pool, or Wildcat Penasco Draw (Yeso) ^{SH-}
12. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT - FORM C-101 FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator
Yates Petroleum Corporation ✓

Address of Operator
207 South 4th Street - Artesia, NM 88210

Location of Well
UNIT LETTER E 2310 FEET FROM THE North LINE AND 990 FEET FROM
THE West LINE, SECTION 6 TOWNSHIP 19S RANGE 25E N.M.P.M.

15. Elevation (Show whether DF, RT, GR, etc.)
3652

6. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☒	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 15" hole at 7:00 PM 9-30-79. TD 358' - Ran 9 joints of 10-3/4" 32.# H-40 ST&C (359') of casing set at 358'. 1-guide shoe at 358', insert float at 318'.. Cemented w/250 sacks of Class C 4% CaCl. PD 8:30 AM 10-1-79. Cement circulated 25 sacks to surface. WOC 12 hours. Cut off, reduced hole to 9 1/2" drilled plug and tested to 600#. OK. Resumed drilling.

TD 968' - Ran 24 jts of 23# K-55 LT&C (968') of casing set at 968'. 1-guide shoe and insert float. 1-centralizer at 928' and 1-centralizer and 1 basket at 500'. Cemented w/200 sacks of Howco Lite 6#/sack gilsonite, 1/4# flocele/sack 2% CaCl and 100 sacks Class C 2% CaCl. PD 6:45 PM 10-2-79. Circulated 30 sacks to surface. WOC 18 hours, NU and tested to 1000#. OK. Reduced hole to 6 1/4", drilled plug and tested to 600#. OK - resumed drilling.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

ICHO. Christine Imbrun TITLE Geol. Secty DATE 10-23-79

APPROVED BY W.A. Gussett TITLE SUPERVISOR, DISTRICT II DATE OCT 26 1979

CONDITIONS OF APPROVAL, IF ANY: