

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

NOV 2 1979

O. C. C.
ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.

OG 783

7. Unit Agreement Name

8. Permit or Lease Name Under

Greasewood BD State

9. Well No.

1 3

10. Field and Pool, or Wildcat Und

Penasco Draw SA-Yessoc

Assoc

12. County

Eddy

SUNDY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

207 South 4th Street - Artesia, NM 88210

4. Location of Well

UNIT LETTER D 990 FEET FROM THE North LINE AND 990 FEET FROM

THE West LINE, SECTION 6 TOWNSHIP 19S RANGE 25E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)

3645.2 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND ABANDONMENT ☐

FULL OR ALTER CASING ☐

CHANGE PLANS ☐

CASING TEST AND CEMENT JOBS ☒

OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1503.

Spudded a 15" hole at 1:30 PM 10-17-79.

TD 321' - Ran 8 joints of 10-3/4" 32.7# H-40 ST&C casing (321') of casing set at 321'. Guide shoe at 321'. Insert float at 281'. Cemented w /250 sacks of Class C 4% CaCl cement PD 2:15 AM 10-18-79. Circulated 75 sacks to surface. WOC 12 hours, backed off and reduced hole to 9 1/2", drilled plug and tested to 600#. OK. Resumed drilling.

TD 960' - Ran 19 joints (766') of 7" 23# K-55 LT&C casing and 5 joints (194') of 7" 20# J-55 ST&C casing set at 960'. 1-Guide shoe at 960' and insert float at 940'. Cemented w/150 sacks RFC, 5# Coloite, 1/4# celloflakes, 2% CaCl, followed by 300 sacks 50-50 Pox "C", 6# Cololite, 1/4# celloflakes, 2% CaCl. 100 sacks Class C 2% CaCl. PD 6:30 AM 10-19-79. Cement did not circulate. WOC 6 hours ran Temperature Survey and found top of cement at 660'. Ran 1", tagged cement at 640'. Spotted 25 sacks of Class C 4% CaCl at 640'. WOC 2 hours, tagged cement at 600', spotted 50 sacks of Class C 4% CaCl at 600'. WOC 2 hours, tagged cement at 475', loaded hole w/water, mixed 120 sacks of Class C 4% CaCl. Cement circulated 5 sacks to surface. WOC 18 hours, NU and tested to 1000#. OK. Reduced hole to 6 1/4", drilled plug and tested to 600#. OK and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Imbrinson

TITLE Geol. Secty

DATE 11-1-79

APPROVED BY W. A. Gussert

TITLE SUPERVISOR, DISTRICT II

DATE NOV 5 1979