

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Amoco Prod. Co.</i>		Lessee <i>Parino Com.</i>		Well # <i>1</i>	
Location of Well	Unit/ <i>19805 660 e</i>	Section <i>23</i>	Township <i>19</i>	Range <i>25</i>	County <i>Eddy</i>
Drilling Contractor			Type of Equipment <i>Rotary to start 10-29-79</i>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>17 1/2</i>	<i>13 7/8</i>	<i>48</i>		<i>400</i>	<i>cin.</i>
<i>12 1/4</i>	<i>9 7/8</i>	<i>40</i>		<i>2500</i>	<i>cin.</i>
<i>8 7/4</i>	<i>5 1/2</i>	<i>17-20+23</i>		<i>9500</i>	

Casing Data:

Surface joints of *9 5/8* inch *36* # Grade *K-55*

(Approved) (Rejected)

Inspected by *M.S.* date *11/13/79*

Cementing Program

Size of hole *10 1/4* Size of Casing *9 5/8* Sacks cement required

Type of Shoe used *guide* Float collar used *yes* Btm 3 jts welded *yes*

TD of hole *2500* Set *2500* Feet of *1 1/2* Inch *36* # Grade *K-55*

New-used csg. @ *2500* with *200* sacks neat cement around shoe

+ *1000* sack *Half Dye* additives *5# gelsolite, 2# salt, 1/4# flocc*

Plug down @ *5:45* (AM) (PM) Date

Cement circulated No. of Sacks

Cemented by Witnessed by

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: *T 300 at the set 5# gelsolite, 1/4# flocc*

Last circ. at No