

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE	1	
FILE	1	✓
U.S.G.S.		
LAND OFFICE		
OPERATOR	1	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEELEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-		7. Unit Agreement Name
Name of Operator Amoco Production Company ✓		8. Farm or Lease Name Parino Com.
Address of Operator P. O. Box 68, Hobbs, NM 88240		9. Well No. 1
Location of Well UNIT LETTER <u>I</u> <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>23</u> TOWNSHIP <u>19-S</u> RANGE <u>25-E</u> NMPM.		10. Field and Pool, or Wildcat Wildcat Morrow
15. Elevation (Show whether DF, RT, GR, etc.) 3417.2 GR		12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Corrected Report

Drilled to a TD of 2501' and ran 9-5/8" 36# K-55 ST&C casing set at 2501'. Cemented with 1000 sx Haliburton Lite cement with 5# Gilsonite/sx and 1/4# Flocele/sx and 8# salt/sx and 300 sx Kwik set cement with 5# Gilsonite/sx and 1/4# Flocele/sx and 2% CACL and 200 sx Class C Incor cement with 2% CACL. Plugged down 5:45 P.M. 11-16-79. Circulated 315 sx. WOC 18 hrs. Tested casing with 1000# for 30 min. Test OK. Reduced hole to 8-3/4" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Bob Davis</u>	TITLE <u>Assist. Admin. Analyst</u>	DATE <u>12-19-79</u>
APPROVED BY <u>W. A. Gussert</u>	TITLE <u>SUPERVISOR, DISTRICT #</u>	DATE <u>DEC 21 1979</u>

CONDITIONS OF APPROVAL, IF ANY:
0+4 NMOCD-A, 1-Hou, 1-Susp, 1-BD