

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

RECEIVED BY
OCT 13 1983
O. C. D.
ARTESIA, OFFICE

8. Indicate Type of Lease
State ☐ Fee ☒
9. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - I" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Reentry	7. Unit Agreement Name
2. Name of Operator Chama Petroleum Company	8. Farm or Lease Name Parino
3. Address of Operator P.O. Box 31405, Dallas, Texas 75231	9. Well No. 1
4. Location of Well UNIT LETTER <u>1</u> <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>23</u> TOWNSHIP <u>19S</u> RANGE <u>25E</u> N.M.P.A.	10. Field and Pool, or Wldent Und. Boyd Morrow
15. Elevation (Show whether DF, RT, GR, etc.) 3417.2 GL	12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER Activity & 4 1/2" casing <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10-2-83: Moved In & Rigged Up

10-3-83: Drilling cement plugs at 3806'

10-4-83: Drilling cement plugs at 7830'

10-5-83: Drilling cement plugs at 8882'

10-6-83: T.D. 9460', cemented total 236 joints (9470'), (47 joints 4 1/2" OD 8rd. 11.60#, LT&C N-80 (1968') & 189 joints 4 1/2" OD 8rd. 11.60#, LT&C J-55 (7502')), 9470' set at 9460' KB, Cemented with 950 sacks Class H 50/50 pozmix containing 4/10 of 1% Hallad 22, 1/4# flocele & 2% gel followed with 425 sacks Class H cement containing 4/10 of 1% CFR-2, 5/10 of 1% Hallad 22 & 3% KCL, plugged down with 3% KCL water, float held, waited on cement 1 1/2 hrs., ran temperature survey which indicated top of cement outside 4 1/2" casing at 4500' from surface

10-7-83: T.D. 9460', released rig at 12:00 A.M. (Midnight) New Mexico Time.

10-8-83: Waiting on Completion

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Kathie Craft TITLE Production Secretary DATE 10/10/83

APPROVED BY _____ TITLE Original Signed By
Leslie A. Clements DATE OCT 13 1983
Supervisor District II

CONDITIONS OF APPROVAL, IF ANY: