

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.O.S.	
LAND OFFICE	
OPERATOR	1

RECEIVED

JAN 11 1980

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. LG-5096
7. Unit Agreement Name
8. Farm or Lease Name Eddy "IL" State Com
9. Well No. 1
10. Field and Pool, or Wildcat Undes. Winchester Morrow
12. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER-
ARTESIA, OFFICE

2. Name of Operator
GULF OIL CORPORATION

3. Address of Operator
P.O. Box 670, Hobbs, NM 88240

4. Location of Well
UNIT LETTER E 1980 FEET FROM THE North LINE AND 660 FEET FROM
THE West LINE, SECTION 30 TOWNSHIP 19S RANGE 29E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
3323' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/> surface	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 17½" hole @ 1A, 1-5-80; drilled to 378' @ 12 noon 1-6-80. Ran 9 jts & 1 cut jt 13-3/8" 48# H-40 ST&C csg (362'); set @ 378'. Cmdt by Halco w/150 sx thickset w/10# Gilsonite & ½# flocele followed by 300 sx Class "H" w/2% CaCl₂. Plug dn @ 5P 1-6-80. Circ 10 sx cmt. Test csg to 500# for 30 min - held OK. WOC total 19 hrs. Drilled cmt & plug; began drlg form @ 3P, 1-7-80 w/12½" hole.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Area Drilling Superintendent DATE 1-10-80

APPROVED BY W.A. Gressitt TITLE SUPERVISOR, DISTRICT II DATE JAN 14 1980

CONDITIONS OF APPROVAL, IF ANY: