

NO. OF COPIES RECEIVED	8
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	2
LAND OFFICE	1
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

NOV 13 1979

O. C. C.
ARTESIA, OFFICE

30-015-23066

Form C-101
Revised 1-1-65

SA. Indicate Type of Lease	STATE ☒ FEE ☐
State Oil & Gas Lease No.	E2943

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. Type of Work		2. Well Identification	
b. Type of Well DRILL ☒ DEEPEN ☐ PLUG BACK ☐ GAS ☒ SINGLE ZONE ☐ OTHER ☐ MULTIPLE ZONE ☐		3. Well Name NA	
4. Operator THRESHOLD DEVELOPMENT COMPANY		5. Leaseholder Conoco State Co	
6. Location 608 Gihls Tower West, Midland, Texas 79701		7. Well Type Wildcat	
8. Direction ONE LETTER I LOCATED 1980 FEET FROM THE South LINE		9. Well Depth 1	
10. Direction AS 660' FEET FROM THE East LINE OF SEC. 10 TWP. 19S RCP. 29E		11. Well Name Eddy	
12. Depth 3374.8' GL		13. Depth 12,000'	
14. Cement Blanket, Effective		15. Cement Morrow	
16. Cement Cactus		17. Cement Rotary	
18. Date November 18, 1979			

PROPOSED CASING AND CEMENT PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
17-1/2"	13-3/8	48	400+	425+	Surface
11"	8-5/8	24	2700+	925+	Surface

The well will be spud with a 17-1/2" hole and drilled to 400'+. Surface casing will be run and cement circulated to surface. Casing will be tested to 1000 psi before drilling out of surface. BOP's will be installed and pressure tested to 3000 psi. (BOP's will be pressure tested a minimum of once every 10 days). An 11" hole will be drilled to 2700'+ and 8-5/8" O.D. casing set and cemented to the surface. Casing will be tested to 1000 psi before drilling out. An 7-7/8" hole will be drilled to a total depth of 12,000'+. If the well is deemed productive, 5-1/2" O.D. casing will be run and cemented with 650+ sacks cement.

Gas Partly Dedicated

APPROVAL VALID
FOR 90 DAYS UNLESS
DRILLING COMMENCED

EXPIRES 2-19-80

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE, GIVE ADEQUATE PREVENTER PROGRAM, IF ANY.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed [Signature] Title AGENT Date 11-12-79

(This space for State Use)

APPROVED BY [Signature] TITLE SUPERVISOR, DISTRICT II DATE NOV 19 1979

CONDITIONS OF APPROVAL, IF ANY:

Cement must be circulated to
surface behind 13 3/8" & 8 5/8" casing