Yates Petroleum Corporation Rio Penasco "MF" Federal 1 1980' FNL and 1980' FWL Section 11-T19S-R25E Eddy County, New Mexico

NOV 2 6 1979

E.C.C. ARTESIA, OFFICE

In conjunction with Form 9-331C, Application for Permit to Drill subject well, Yates Petroleum Corporation submits the following ten items of pertinent information in accordance with USGS requirements:

- The geologic surface formation is gravels.
- The estimate tops of geologic markers are as follows: 2.

Grayburg 380' San Andres 813' Glorieta Sd 2363' Wolfcamp 5700'	Strawn Atoka Morrow Chester LS T.D.	8087' 8690' 8965' 9288' 9348'
--	---	---

3. The estimated depths at which anticipated water, oil, or gas formations are expected to be encountered:

Gravels 0-400'; 950-1200';5700-6600'; 7750-7900' Water:

2360' - 2750 Oil or Gas:

86901 - 8800 9000! - 9288

- Proposed Casing Program: See Form 9-331C.
- Pressure Control Equipment: See Form 9-331C and Exhibit B.
- Mud Program: See Form 9-331C.
- Auxiliary Equipment: Kelly Cock; pit level indicators and flow sensor equipment; 7. sub with full-opening valve on floor, drill pipe connection.
- Testing, Logging and Coring Program: 8.

Samples: Surface casing to T.D.

As Warranted DST's:

Intermediate casing to T.D. Logging:

CNL-FDC T.D. to casing with GR-CNL on to surface and Coring:

DLL from T. D. to casing with selected min. $R_{\mathbf{x}}\mathbf{0}\text{.}$

- No abnormal pressures or temperatures are anticipated. 9.
- 10. Anticipated starting date: As soon as possible after approval.