

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.
NM-12833

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Rio Penasco MF Fed. Com.

9. WELL NO.
1

10. FIELD AND POOL, OR WILDCAT
Unders ^{Board} Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 11-19S-25E
Unit F NMPM

12. COUNTY OR PARISH
Eddy

13. STATE
NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR
Yates Petroleum Corporation

3. ADDRESS OF OPERATOR
207 South 4th Street - Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface
1980' FNL & 1980' FWL of Section 11-19S-25E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3453.9' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF <input type="checkbox"/>	PULL OR ALTER CASING <input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	MULTIPLE COMPLETE <input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	ABANDON* <input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
(Other) <input type="checkbox"/>	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF <input type="checkbox"/>	REPAIRING WELL <input type="checkbox"/>
FRACTURE TREATMENT <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
SHOOTING OR ACIDIZING <input type="checkbox"/>	ABANDONMENT* <input type="checkbox"/>
(Other) <u>Set Production Csg.</u> <input checked="" type="checkbox"/>	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 9363' - Ran 228 joints of 5 1/2" 17# & 15.5# N-80 and K-55 LT&C casing as follows: 23 joints N-80 17# (759'); 46 joints 17# K-55 (2041'); 139 joints 15.5# (5723'); 20 joints 17# K-55 (864') (Total 9387') of casing set 9357'. 1-Guide shoe at 9357'. Diff-fill float collar at 9326'. Used 12 centralizers. Cemented w/250 gallons mud flush, 415 sacks Howco Lite 3/10% Halad-22, 6/10% CFR-2, 5#/sack KCL. Tailed in w/150 sacks Class "H", 3/10% CFR-2, 5/10% CFR-2, 5#/sack KCL. Displaced w/60 bbls KCL water. PD 3:40 PM 1-19-80. WOC and tested to 1500#. OK. Ran Temperature Survey and found top of cement at 6910'; WLPBTD 9346'.

RECEIVED

JAN 23 1980

O. C. S.
ARTESIA OFFICE

RECEIVED

JAN 24 1980

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Christine Johnson TITLE Geol. Secty. DATE 124-80

(This space for Federal or State office use)

APPROVED BY (Orig. Sgd.) GEORGE H. STEWARD TITLE Geological Engineer DATE JAN 24 1980

CONDITIONS OF APPROVAL, IF ANY: