

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>McClellan oil Corp.</i>		Lease <i>Fres Amigos</i>		Well # <i>1</i>	
Location of Well	Unit <i>19803 660 W</i>	Section <i>9</i>	Township <i>19</i>	Range <i>23</i>	County <i>Eddy</i>
Drilling Contractor	<i>W E K Drilling Co.</i>		Type of Equipment <i>Rotary to start approx. 12-26-79</i>		

APPROVED CASING PROGRAM

* *Witness*

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>17 1/2"</i>	<i>13 7/8"</i>	<i>54</i>		<i>250</i>	<i>275 lbs.</i>
<i>12 1/4"</i>	<i>8 7/8"</i>	<i>24</i>		<i>1700</i>	<i>2 lbs.</i>
<i>7 7/8"</i>	<i>5 1/2"</i>	<i>15 1/2 + 17</i>		<i>7800</i>	<i>1200</i>

Casing Data:

Surface _____ joints of *8 5/8* inch *24* # Grade *K-55*
(Approved) (Rejected) _____

Inspected by *M.S.* date *2/4/80*

Cementing Program

Size of hole *12 1/4* Size of Casing *8 5/8* Sacks cement required _____

Type of Shoe used *guide* Float collar used *insert* Btm 3 jts welded *yes*

TD of hole *1730* Set *1710* Feet of *8 5/8* Inch *24* # Grade *K-55*

New-used csg. @ *1710* with *200* *2 1/2* sacks neat cement around shoe

+ *200* sack *Thix* and additives *1/4 # coloflores*

Plug down @ *8:30* (AM) (PM) Date *2/6/80*

Cement circulated *No* No. of Sacks *-0-*

Cemented by *Western Cementing* Witnessed by *Mike Stiffel*

Temp. Survey ran @ *1330* (AM) (PM) Date *2/6/80* top cement @ *910*

Casing test @ _____ (AM) (PM) Date *Tagged toe @ 1662' inside casing.*

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: *+500sx pacacetting light (10% salt - 1/4 # coloflores)*

lost circ. @ 700'

centralizers @ 1610'-1690' *lost cement @ 997'*