

m 9-331
May 1963UNIT STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPlicate
(Other instructions on
verse side)Form approved.
Budget Bureau No. 42 R1424.
5. LEASE DESIGNATION AND SERIAL NO.

NM 34647

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back **RECEIVED** reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐ **FEB 22 1980**

2. NAME OF OPERATOR **O. C. D.**

3. ADDRESS OF OPERATOR **ARTESIA, OFFICE**

2525 N.W. Expressway, Oklahoma City, OK 73112

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

Unit Letter **E.** 1980' FNL & 660' FEL

14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)

Permit Date **12/11/70****3575'**

7. UNIT AGREEMENT NAME

NA

8. FARM OR LEASE NAME

Charlotte McKay Federal

9. WELL NO.

10. FIELD AND FOOT OR WILDCAT

Wildcat11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA**Sec. 25-T20S-R24E**

12. COUNTY OR PARISH 13. STATE

Eddy**New Mexico**

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) **Drilling Operations** ☒

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Drld. 27" hole to 35'. Ran 20" csg. to 35', cmt w/3 yards of redimix.
2. Drld 17½" hole to 412'. Ran 13 3/8", 54.5# csg. Cs. seat 355', (Csg. stuck at 355'; free at 316') Dia-Log perf 13 3/8" csg. w 4 holes 311-314'. Dowell cmt w/400 sx class "C". Ran temp. survey. T.O.C. 250'.
3. Dowell Cemented down annulus w/520 sx of class "C". Circ. back to surface. Tested to 1500#.
4. Drld. 12¼" hole to 2000'. Ran, 8 5/8", 24# csg; Cs 2000'; cmt w/980 sx class "C". Circ. approx. 186 sx. NU BOP & tested to 1500#.
5. Drld. 7 7/8" hole to 9690' TD. Schlumberger ran DLL-GR from 9678' - 2000' & CNL-FDC-GR-CAL 9578' to surface. Ran 5½" csg. Cs 9690'; Dowell cmt w/300 sx 50-50 Light Poz 3 & 350 sx Self Stress Cmt. Ran temp. survey, TOC 5700'. Cut 5½" csg & NU Tree.
6. Released rig 1/21/80.

RECEIVED**FEB 21 1980****U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO**

18. I hereby certify that the foregoing is true and correct

SIGNED

Jeanie OwensTITLE **Prod. Staff Assoc. II**DATE **2/12/80**

(This space for Federal or State office use)

APPROVED BY

(Orig. Sgd.) GEORGE H. STEWARTTITLE **ACTING DISTRICT ENGINEER**

DATE

FEB 21 1980

CONDITIONS OF APPROVAL, IF ANY: