

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Southland Royalty Co.</i>		Lease <i>JEB Stewart 13 Com.</i>		Well # <i>1</i>	
Location of Well	Unit <i>19805 1980e</i>	Section <i>13</i>	Township <i>19</i>	Range <i>27</i>	County <i>Eddy</i>
Drilling Contractor <i>Hondo Dry Co.</i>			Type of Equipment <i>Rotary & Start approx. 1-18-80</i>		

APPROVED CASING PROGRAM

* *Witness*

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>17 1/2"</i>	<i>13 3/8"</i>	<i>48</i>		<i>300</i>	<i>325 circ</i>
<i>12 1/4</i>	<i>9 5/8"</i>	<i>36</i>		<i>2400</i>	<i>1100 "</i>
<i>8 3/4</i>	<i>4 1/2"</i>	<i>11.6</i>		<i>11200</i>	<i>1100</i>

Casing Data:

Surface _____ joints of *9 5/8* inch *36* # Grade *K-55*
(Approved) (Rejected) _____

Inspected by *M.S.* date _____

Cementing Program

Size of hole *12 1/4* Size of Casing *9 5/8* Sacks cement required _____

Type of Shoe used *guide* Float collar used *yes* Btm 3 jts welded *yes*

TD of hole *2400'* Set *2400'* Feet of *9 5/8* Inch *36* # Grade *K-55*

New-used csg. @ *2400'* with *200* 2 1/2 sacks neat cement around shoe

+ *650* sax *C low dense* additives *5# gilsonite, 5# salt, 1/4# celoflokes*

Plug down @ *7:15* (AM) (PM) Date *2/21/80*

Cement circulated *yes* No. of Sacks *50*

Cemented by *BJ. Hughes* Witnessed by *Michael Stillfield*

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____

centralizers @ 2320'-2280'-2240'

Full returns to 2400'